

THIS IS A C.A.D. GENERATED DRAWING TOLERANCE UNLESS OTHERWISE SPECIFIED DO NOT MAKE MANUAL REVISIONS TO MASTER. .X ±0.25

.XX ±0.13 .XXX ±0.05










NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

STEEL, NICKEL PLATED

THERMOPLASTIC POLYESTER, UL94V-0 COPPER ALLOY, 30µ" GOLD PLATED



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

COMPLIANT

SIGNAL CONTACT RESISTANCE:	10mΩ MAX.
SIGNAL CONTACT CURRENT RATING:	5A PER CONTACT
(IF PRESENT)	
POWER/CO-AX CONTACT RATING:	10A (CURRENT)


INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE:

OPERATING TEMPERATURE:

5000MΩ min.

-55°C ~ 125°C

1000V AC rms



					SW REFERENCE NO.: 629 COMBO ASSEMBLY						
			DRAWN: C.B			DATE: JAN. 01/201			19		
			CHECKED:		DATE:						
	EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND	SCALE:	(IN C.A.D. 1:1)		SHEET	1	OF	2		
	YOUR CONNECTION TO C	TORONTO, ONTARIO CANADA	MANUFACTURE OR SALE OF APPARATUS	DRAWING NUMBER: 629-5W5-			-640-1N4			ISSUE	
YOUR		QUALITY & SERVICE		PART NUM	IBER: 629	9-5W5-	640-1N4			1	

