	т G т т	
Image: standard lasted on Micro		
Activities and and the stand of the sta		
CHARACTERISTICS Shadard: Based on MIL-DTL-38999 Series III Shadard: Based on MIL-DTL-38999 Series III Shadard: Based on MIL-DTL-38999 Series III Shell Plating: Nickli -insulator Timemoplastic -insulator ComaceCor dimension -insulator Comace Copy Alloy -Seals & Grommet Sill Contact Same -Seals & Grommet Sill Contact Same -Oritact Same Sill Contact Same -Seals & Grommet Sill Contact Same -Delivered without Souriau contacts - -Temperature Range: - -Sill Sprature Range: - - - - - - - - - - - - - - -		LAYOUT SHOWN AS EXAMPLE
-Standard : Based on ML-DT-38999 Series III -Standard : Based on ML-DT-38999 Series III -Shell Matierial : Aluminium -Shell Matierial : Aluminium -Shell Matierial : Nickel -Insulator : Thermopatatic -Contacts : Copper Alloy -Seals & crommet : Slickon Elastomer -Contact Plating : Cold over copper Alloy 0.8µm minimum -Ourability : Sold Mating cycles -Delivered without Souriau contacts - -Temperature Range : - 657 Cto +200°C -Salt Spray : 48 hours -Mass : 29.9 g ± 10% Basic SERIES: 8D 5 SHELL TYPE : Fileworth Rri Shielding - Contact Trutpe : Slickul Delivered W//O Contacts SHELL TYPE : Slickul - Delivered W//O Contacts SHELL SZE : 17 Phateires SHELL SZE : 17 Intrust to be reprodued or communicated withou comminiticat withou property of shield	Keying Shown as example	
Shell Material A uninitum Shell Material A uninitum Shell Plating Nickel Insulator Thermoplastic -contacts Copper Alloy Seals & Grommer Silcon Elastomer -contact Plating E Gold over copper Alloy 0.8µm minimum -Durability 500 Mating cycles -Derivered without Souriau contacts PN: 8D517F06SBL Temperature Range -65° to +200°C -sakt Spray :48 hours -Mass :29.9 g ± 10% Basic Series: 80 SHELL TYPE :Nigwith RFI Shielding CONTACT TYPE :Sandard Crimp Contact SHELL SZE: 17 CONTACT TYPE: SOCKET(500 Mating): PLATING F NHLL SZE: 17 CONTACT TYPE: SOCKET(500 Mating): PLATING F Nickel	Connector unitension]
Shell Plating : Nickel -shell Plating : Nickel -insulator : Thermoplastic -contacts : Copper Alloy -seals & Grommet : Single Thermoplastic -contact Plating : Gold over copper Alloy 0.8µm minimum -Durability : Soot Mating Crycles - Delivered without Souriau contacts - PN: 8D517F06SBL - Temperature Range : - 55'C to + 200°C - Sail Spray : 29.9 g ± 10% Mass : 29.9 g ± 10% BASIC SERIES: 80 SHELL TYPE : Nickel CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 17 This decontent is the property of summanded crimp Contact PLATING : F = Nickel	ØS 35.7 Max	
-Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Slicon Elastomer -Contact Plating : Gold over copper Alloy 0.8µm minimum -Durability : SJO Mating cycles -Delivered without Souriau contacts - -Temperature Range : 65°C to +200°C -Sait Spray : 48 hours -Mass : 29.9 g ± 10% BASIC SERIES: 8D 8D 5 SHELL TYPE : Net Elsteel CONTACT TYPE : Standard Crimp Contact SHELL TYPE : Souriau BASIC SERIES: 8D 8D 5 SHELL TYPE : Standard Crimp Contact SHELL SIZE : 17 : CONTACT TYPE PLATING : F = Nickel CONTACT TYPE : SoURIAU SOURIAU DRG	2 31 Max	
- Contacts :: Copper Alloy -Seals & Grommet :: Silicon Elastomer - Contact Plating :: Gold over copper Alloy 0.8µm minimum -Durability :: Sold over copper Alloy 0.8µm minimum -Derivered without Souriau contacts -Temperature Range -Temperature Range :: -65°C to +200°C -Salt Spray :: 48 hours -Mass :: 29.9 g ± 10% BASIC SERIES: 80 SHELL TYPE : Neglend By: Delivered W/O Contact: SCALE SHELL TYPE : Standard Crimp Contact SHELL SZE: 17 .: CONTACT TYPE : SOCKET(S00 Matings) PLATING : F = Nickel CONTACT LAYOUT : 17-06 : SOURIAU DRG N°		the Specifications issued by either of the Parties or by a third party
Contact Plating : Gold over copper Alloy 0.8µm minimum -Durability : S00 Mating cycles -Delivered without Souriau contacts -Temperature Range : -65°C to +200°C -Salt Spray : 48 hours -Mass : 29.9 g ± 10% BASIC SERIES: 8D 8D -17 F 06 SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact SHELL SZE : 17 06 PLATING : F PLATING : F PLATING : F	-Contacts : Copper Alloy	(professional recommendation, technical notice.)
-Durability : 500 Mating cycles -Durability : 500 Mating cycles -Delivered without Souriau contacts -Temperature Range : -65°C to +200°C -Salt Spray : 48 hours -Mass : 29.9 g ± 10% BASIC SERIES: 8D 5 -17 F 06 S B L Delivered W/O Contact 07 06 S B L SHELL TYPE : Standard Crimp Contact 07 06 S B L SHELL SZE : 17 Delivered W/O Contact 07 07 SOURIAU WWW.SOURIAU.COM It must not be reprodued or communicated without permission PLATING : F<=	-Seals & Grommet : Silicon Elastomer	
-Delivered without Souriau contacts -Temperature Range : .65°C to +200°C -Salt Spray : .48 hours -Mass : 29.9 g ± 10% BASIC SERIES: <u>8D</u> 5 - <u>17</u> F <u>06</u> S <u>B</u> <u>L</u> <u>Delivered W/O Contacts</u> SHELL TYPE : Plug with RFI Shielding <u>CONTACT TYPE : Standard Crimp Contact</u> <u>SHELL SIZE : 17</u> PLATING : F = Nickel <u>CONTACT TYPE : SOCKET(500 Matings)</u> <u>CONTACT TYPE : SOCKET</u>		FR Not Listed
-Temperature Range : -65°C to +200°C -Salt Spray : 48 hours -Mass : 29.9 g ± 10% BASIC SERIES: 8D 5 - 17 F 06 S B L SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 17 PLATING : F = Nickel CONTACT TYPE : SOCKET(500 Matings) CONTACT TYP		PN: 8D517F06SBI
-Salt Spray : 48 hours -Mass : 29.9 g ± 10% A 14-10-2016 First Release -Mass : 29.9 g ± 10% A 14-10-2016 First Release -MOD N° Designed By: Date: CUSTOMER DRAWING Designed By: Date: CUSTOMER DRAWING Designed By: Date: CUSTOMER DRAWING Designed By: Date: CUSTOMER DRAWING SALE SHELL SIZE : 17 PLATING : F = Nickel CONTACT TYPE : SOCKET(500 Matings) CONTACT TYPE : SOCKET(500 Ma		
-Mass : 29.9 g ± 10% -Mass : 29.9 g ± 10% How services in the property of source in the prop		A 14-10-2016 First Release
Designed By: Date: CUSTOMER DRAWING Designed By: Date: Aluminium Plug 8D series BASIC SERIES: 8D 5 - 17 F 06 S B L SHELL TYPE : Plug with RFI Shielding 0 S B L Delivered W/O Contacts SCALE NPRDS / PROJECT SHELL SIZE : 17 0 SHELL SIZE : 17 ORIENTATION : B SOURIAU This document is the property of SOURIAU.COM SOURIAU PLATING : F = Nickel CONTACT TYPE : SOCKET(500 Matings) FORMAT SOURIAU DRG N° SHEET		ISS DATE Latest modification - by MOD N°
BASIC SERIES: 8D 5 - 17 F 06 S B L SHELL TYPE : Plug with RFI Shielding Delivered W/O Contacts Delivered W/O Contacts NA Image: Contact Type : Standard Crimp Contact SCALE NA Image: Contact Type : Standard Crimp Contact SOURIAU This document is the property of SOURIAU SOURIAU This document is the property of SOURIAU SOURIAU Image: Contact Type : SockET (Ston Matings) Image: Contact Type : SockET (Ston Matings) Image: Contact Layout : 17-06 FORMAT SOURIAU DRG N° This document is the property of Souriact without permission PLATING : F = Nickel Contact Layout : 17-06 FORMAT SOURIAU DRG N° SHEET		
BASIC SERIES. BD SD SD <td></td> <td>TITLE Aluminium Plug 8D series</td>		TITLE Aluminium Plug 8D series
BASIC SERIES. BD S I I/ F Od S B I I// F		SCALE General linear NIDPDS / DPOJECT
SHELL TYPE : Plug with RFI Shielding Delivered W/O Contacts INA Ina <td></td> <td></td>		
SHELL SIZE : 17 CONTACT TYPE : SOCKET(500 Matings) SOURIAU it must not be reproduced or communicated without permission PLATING : F = Nickel CONTACT LAYOUT : 17-06 FORMAT SOURIAU DRG N° SHEET		This document is the property of
SHELL SIZE : 17 CONTACT TYPE : SOCKET(500 Matings) communicated without permission PLATING : F = Nickel CONTACT LAYOUT : 17-06 FORMAT SOURIAU DRG N° SHEET		
	SHELL SIZE : 17 CONTACT TYPE : SOCKET(5	00 Matings) communicated without permission
A3 8D517F06SBL-C 1/2	PLATING : F = Nickel CONTACT LAY	
		A3 8D517F06SBL-C 1/2

r	т	G	г –	m	Ū	0
		Contact Layout				
4		En At				
	-x -	$ \stackrel{E}{\bigoplus} \stackrel{A}{\bigoplus} $ $ \stackrel{D}{\bigoplus} \stackrel{F}{\bigoplus} \stackrel{B}{\bigoplus} $ $ \cdot \times $				
	Conta position A	(mm) (mm) +.121 (3.07) +.209 (5.31)				
ယ	B C D E F	+.000 (0.00)241 (6.12) 241 (6.12) +.000 (0.00) 121 (3.07) +.209 (5.31)				
	size no. co	mber of Size Service Contact Supersedes ntacts contacts rating location 6 12 I All MIS20053-6				
	1					
						SOURIAU shall not be liable for ar due to a use of the Products w the Specifications issued by either o (professional recommenda
N						Count FR
						PN: 8D517
					A 14-10-20 ISS DATE	D16 First Release
					Designed By: TITLE	Date: Alumii
					SCALE	General linear Tolerances:
—					SOURIA	
					FORMAT	SOURIAL
	Н	G	F	E	A3	8D517F
	П	I G				

σ		:	Δ				
					4		
					3		
any non-conformit which does not co r of the Parties or t dation, technical no ntry Jurisd R	mply wit by a thirc otice.)	h I party Control List			2		
7F06SBL				AOD N°			
	CUSTO	OMER DRAWIN					
inium Plug 8D series							
r	NPRDS / PROJECT						
		859		of	1		
.COM	i	his document is the SOURIAU it must not be repro nmunicated withou	oduced o	r			
U DRG N° F06SBL-C	I			SHEET 2/2			
В			A				