	m		0			
Keying S CHARACTERISTICS	Shown as example		LAYOUT SHO	OWN AS EXAMPLE		
-Standard : Based on MIL-DTL-38999 Series III -Shell Material : Composite -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer	DimNominalØS41.7 MaxZ'31.5 MaxVV THREADM31x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)			
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories -Temperature Range : -65°C to +200°C		A 08-10-2016		FR N 0521M39SE	ot Listed	
-Salt Spray : 2000 hours - Mass : 57.1 g ± 10%		ISS DATE Designed By:	Latest modification - by Date:	C	USTOMER DRAWING	MOD N°
		TITLE	Composite Plug 8D series		series	
BASIC SERIES: 8D 5 - 21 M 39 S   SHELL TYPE : Plug with RFI Shielding - 21 M 39 S	E	SCALE	-{	al linear rances: ±	NPRDS / PROJECT 859 This document is the prope	erty of
CONTACT TYPE   : Standard Crimp Contact     SHELL SIZE   : 21	ORIENTATION : E CONTACT TYPE : SOCKET(500 Matings)	SOURIAU	WWW.SOUF	RIAU.COM	SOURIAU it must not be reproduce communicated without perr	d or
PLATING : M = Nickel CONTACT LAYOUT : 21-39		FORMAT A3				SHEET 1/2
H G F	E	D	С	B	A	

