

EFX6(01)-240X240T0800 Aliases (UFSEX6010AT080, EFX6(01)240X240T0800)

KEMET, EFX6, Flex Suppressors, Noise Suppression



General Information		
Series	EFX6	
Style	Sheet	
Description	Flex Suppressor High Permeability Type	
Features	High Permeability Type	
RoHS	Yes	
Qualifications	UL94 HB, UL File No. E176124	
Environment	RoHS Compliant, Halogen Free, PVC Free, Lead Free, Red Phosphorus Free	

Specifications				
Temperature Range	-40/+105°C			
Permeability	160 u At 3MHz			
Effective Frequency	1 MHz to 3GHz			
Specific Gravity	3.8 TYP			
Thermal Conductivity	1.35 typical			
Surface Resistivity	1MOhm/sq. TYP			

Click here for the 3D model.

Dimensions	
Sheet Size	240x240mm
L	240mm NOM
W	240mm NOM
Т	0.1mm NOM

Packaging	Specification
-----------	---------------

Tape Description	Without PET Tape (Txx00)
Tape Thickness	0.03mm
Component Weight	22.77 g

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.