


F161SG104M063A Obsolete

F161, Film, Metallized Polyester Stacked, Automotive Grade, 0.1 uF, 20%, 40 VAC, 63 VDC, 100°C, 2824, 2.5mm



Note: '()' correspond to the letters used in the product bulletin

Dimensions	
Chip Size	2824
L	7.3mm +/-0.2mm
W	6mm +/-0.2mm
Т	2.5mm +/-0.2mm
F	0.5mm NOM

Packaging Specifications	
Packaging	Bulk, Bag
Packaging Quantity	2000

General Information		
Series	F161	
Dielectric	Metallized Polyester Stacked	
Style	SMD Chip	
Features	Automotive Grade	
RoHS	Yes	
Qualifications	AEC-Q200	
AEC-Q200	Yes	
Miscellaneous	This Capacitor Is Currently Under Development, Please Contact KEMET For Availability.	
Shelf Life	104 Weeks	
MSL	3	

Specifications	, ,
Capacitance	0.1 uF
Capacitance Tolerance	20%
Voltage AC	40 VAC
Voltage DC	63 VDC
Temperature Range	-55/+100°C
Rated Temperature	100°C
Dissipation Factor	0.8% 1kHz, 1.2% 10kHz, 2.5% 100kHz
Insulation Resistance	1GOhms
Max dV/dt	30 V/us

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.