

LINEAR TECHNOLOGY MATERIALS DECLARATION

ltc2960cdc-1#trpbf

(Engineering Calculation)

DFN 2mm X 2mm Exp. Pad

(printed on: 2020-07-11 17:42:47)

TOTAL MASS (g) : 0.009098

| COMPONENT MATERIAL | VENDOR/ INDUSTRY NAMES | CONSTITUENT NAME | CAS NUMBER | CONSTITUENT MASS (g) | CONSTITUENT (PPM) OF MATERIAL | CONSTITUENT (PPM) OF TOTAL PKG. | | |
|--------------------------|----------------------------------|--------------------------------|------------|----------------------|-------------------------------|---------------------------------|----------------|----------------------|
| Active Device | Linear Technology | Silicon (Si) | 7440-21-3 | 0.000454 | 1000000 | 49899.296875 | | |
| Die Coat | Dow Corning | Silicone | 69430-27-9 | 0.000000 | 0 | 0 | | |
| Lead Frame | Cu | Copper (Cu) | 7440-50-8 | 0.002935 | 975000 | 322586.875 | | |
| | | Iron (Fe) | 7439-89-6 | 0.000072 | 24000 | 7913.54492188 | | |
| | | Phosphorus (P) | 7723-14-0 | 0.000001 | 300 | 109.910339355 | | |
| | | Zinc (Zn) | 7440-66-6 | 0.000002 | 700 | 219.820678711 | | |
| | | Nickel (Ni) | 7440-02-0 | 0.000000 | 0 | 0 | | |
| | | Silicon (Si) | 7440-21-3 | 0.000000 | 0 | 0 | | |
| | | Magnesium (Mg) | 7439-95-4 | 0.000000 | 0 | 0 | | |
| | | Tin (Sn) | 7440-31-5 | 0.000000 | 0 | 0 | | |
| Lead Frame Total: | | | | 0.003010 | 1000000 | 330830.125 | | |
| Plating | PMI | Exter. Plating Pb | 7439-92-1 | 0.000000 | 0 | 0 | | |
| | | Exter. Plating Sn | 7440-31-5 | 0.000136 | 1000000 | 14983.5048828 | | |
| | | External Plating Total: | | | | 0.000136 | 1000000 | 14983.5048828 |
| | | Inter. Plating Ni | 7440-02-0 | 0.000000 | 0 | 0 | | |
| | | Inter. Plating Ag | 7440-22-4 | 0.000072 | 1000000 | 7913.54492188 | | |
| | | Internal Plating Total: | | | | 0.000072 | 1000000 | 7913.54492188 |
| Die Attach | ELECTRICALLY CONDUCTIVE ADHESIVE | Silver (Ag) | 7440-22-4 | 0.000147 | 800000 | 16156.8203125 | | |
| | | Tin (Sn) | 7440-31-5 | 0.000000 | 0 | 0 | | |
| | | Lead (Pb) | 7439-92-1 | 0.000000 | 0 | 0 | | |
| | | Silica (SiO2) | 60676-86-0 | 0.000000 | 0 | 0 | | |
| | | Indium (In) | 7440-74-6 | 0.000000 | 0 | 0 | | |
| | | Metal Oxide | | 0.000000 | 0 | 0 | | |
| | | Antimony (Sb) | 7440-36-0 | 0.000000 | 0 | 0 | | |
| | | Resin (EP) | | 0.000037 | 200000 | 4066.68286133 | | |
| Die Attach Total: | | | | 0.000184 | 1000000 | 20223.5039062 | | |
| Encapsulation | MULTI-AROMATIC RESIN Br/Sb FREE | Resin (EP) | | 0.000677 | 130000 | 74409.296875 | | |
| | | Bromine (Br) | 40039-93-8 | 0.000000 | 0 | 0 | | |
| | | Silica (SiO2) | 60676-86-0 | 0.004481 | 860000 | 492508.21875 | | |
| | | Antimony Trioxide (Sb2O3) | 1309-64-4 | 0.000000 | 0 | 0 | | |
| | | Metal Hydroxide | | 0.000000 | 0 | 0 | | |
| | | Carbon Black (C) | 1333-86-4 | 0.000052 | 10000 | 5715.33740234 | | |
| | | Encapsulation Total: | | | | 0.005210 | 1000000 | 572632.9375 |
| Bond Wire Estimated | AFW/TANAKA/ Kn | Gold (Au) | 7440-57-5 | 0.000032 | 1000000 | 3517.13085938 | | |
| | | | | | TOTAL MASS (g) : | 0.009098 | | |