




## VMDTC20-15-M6-70-Z/10PK

Ruland VMDTC20-15-M6-70-Z/10PK, Vibration Isolation Mount, 20mm OD, M6 Tapped Holes, 6mm Tapped Hole Depths, 15mm Height, 70 Shore A Natural Rubber Jacket, Steel

10 pack



### Description

Ruland VMDTC20-15-M6-70-Z/10PK is a 10 pack of vibration isolation mounts, each with two tapped holes. An individual isolation mount has a 20mm outside diameter, M6 tapped holes, 6mm tapped hole depths, and 15mm height. Vibration isolation mounts are used to dampen shock loads and reduce noise and wear on industrial equipment such as motors, conveyors, compressors, fans, or pumps which allows for a safer and more pleasant working environment. They are often referred to as a sandwich mount or rubber buffer because they function as a shock or vibration isolator sandwiched between two machine components or surfaces. A vibration isolation mount can be mounted to the system by threading it onto an existing stud on the components. The rubber jackets are made from natural rubber which has good elasticity and is well suited for most industrial equipment. Vibration isolation mounts in this pack have 70 Shore A hardness for the greatest rigidity and load capacity. Bodies are made from zinc plated steel allowing for high strength suitability in most industrial applications. These vibration isolation mounts are manufactured by Otto Ganter, inventoried by Ruland, and RoHS3 compliant.

### Product Specifications

<b>Outer Diameter (OD)</b>	0.79 in (20 mm)	<b>Height (H1)</b>	0.59 in (15 mm)
<b>Thread (TH)</b>	M6 x 1.0	<b>Plate Thickness (PT)</b>	0.08 in (2 mm)
<b>Tapped Hole Depth (LT)</b>	0.24 in (6.1 mm)	<b>Spring Rate</b>	2084.2 lb/in (365 N/mm)
<b>Shore Hardness</b>	70A (+/- 5)	<b>Max Deflection</b>	0.06 in (1.5 mm)
<b>Max Axial Load</b>	123.64 lb (550 N)	<b>Multipack Quantity</b>	10
<b>Geometry</b>	Cylindrical	<b>Rubber Material</b>	Natural Rubber
<b>Metal Material</b>	Zinc Plated Steel	<b>Metallic Body Finish</b>	Zinc-Plated
<b>Country of Origin</b>	Hungary	<b>Weight (lbs)</b>	0.291500
<b>UPC</b>	634529359334	<b>Tariff Code</b>	4016.99.6000
<b>UNSPC</b>	31162804		

**Note 1** Performance ratings are for guidance only. The user must determine suitability for a particular application.