



SECT. A-A



SECT. B-B



SECT. C-C

注記 NOTES:
 1. 一般公差 : ±0.4
 GENERAL TOLERANCES: ±0.4

ニッケル (2 μm MIN.) 下地 金 (0.35 μm MIN.) GOLD (0.35 μm MIN.) OVER NICKEL (2 μm MIN.)	無 NO	VO	39-00-0314	I38 IAGL	バラ端子 LOOSE
	有 YES	VO	39-00-0312	I38 IAG	連鎖状端子 CHAIN
銅 (3 μm MIN.) 下地 錫 (0.5 μm MIN.) OVER TIN (0.5 μm MIN.) OVER COPPER (3 μm MIN.)	無 NO		39-00-0313	I38 IGL	バラ端子 LOOSE
	有 YES		39-00-0311	I38 IG	連鎖状端子 CHAIN
銅 (0.5 μm MIN.) 下地 錫 (0.9 μm MIN.) OVER TIN (0.9 μm MIN.) OVER COPPER (0.5 μm MIN.)	無 NO		39-00-0310	I38 IAT2L	バラ端子 LOOSE
	有 YES		39-00-0309	I38 IAT2	連鎖状端子 CHAIN
メッキ PLATING	無 NO		39-00-0308	I38 IATL	バラ端子 LOOSE
	有 YES		39-00-0284	I38 IAT	連鎖状端子 CHAIN
ディンプル有無 WITH DIMPLE	無 NO		39-00-0307	I38 ITL	バラ端子 LOOSE
	有 YES		39-00-0285	I38 IT	連鎖状端子 CHAIN
			EDP.NO.	ENG.NO.	形状 FORM

REDRAW EC NO: J2015-0741 DRWN: YWAKE 2015/01/14 CHKD: KASAKAWA 2015/01/14 APPR: NUKITA 2015/01/15	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE		SCALE		DESIGN UNITS		THIRD ANGLE PROJECTION	
	0.25 UNDER UNDER ±0.03		MM ONLY		---		METRIC		◎ □	
	0.25 OVER 0.5 UNDER ±0.05		DRAWN BY DATE		TITLE					
	0.5 OVER 1.0 UNDER ±0.1		YWAKE 2015/01/14		.093 DIA. FEMALE TERM.					
1.0 OVER 10 UNDER ±---		CHECKED BY DATE								
10 OVER 30 UNDER ±---		KASAKAWA 2015/01/14								
30 OVER ±---		APPROVED BY DATE								
ANGULAR ±--- °		NUKITA 2015/01/15								
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		MATERIAL NO.		SEE TABLE		DOCUMENT NO.		SHEET NO.		
		A3		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		SD-1381-001		11 OF 1		

材料 MATERIAL	黄銅 BRASS 0.264t
適用電線範囲 WIRE RANGE	AWG#18-#24
被覆外径 INS. RANGE	φ 1.5~3.1