

## Fuse - SI FORM C 25 A DIN 72581 - 0913757

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Flat-type plug-in fuse, type C, color code: white, nominal current: 25 A

### Your advantages

- ✓ With snap-in foot for secure pre-assembly on the PCB
- ✓ Fuse holder for flat-type fuses with a maximum nominal voltage of 32 V

### Key Commercial Data

Packing unit	50 pc
GTIN	 4 017918 104016
GTIN	4017918104016

### Technical data

#### General

Color	white
Flammability rating according to UL 94	V0
Fuse	C
Nominal current $I_N$	25 A
Nominal voltage $U_N$	24 V

#### Dimensions

Width	5 mm
Length	19 mm

#### Standards and Regulations

Flammability rating according to UL 94	V0
--	----

### Approvals

Approvals

# Fuse - SI FORM C 25 A DIN 72581 - 0913757

## Approvals

---

Approvals

EAC / EAC

---

Ex Approvals

---

## Approval details

EAC		EAC-Zulassung
-----	---	---------------

EAC		RU C- DE.A*30.B.01742
-----	---	--------------------------

---

Phoenix Contact 2019 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>