


# 12-Outlet Vertical Power Strip, 120V, 20A, Hardwired Input, 36 in.

MODEL NUMBER: PS3612-20HW



#### **Highlights**

- AC input hardwired via knockout on unit
- 12 outlets
- 20-amp capacity
- Ideal for applications requiring permanent installation

### **Package Includes**

- PS3612-20HW
- Instruction manual

## Description

Tripp Lite's PS3612-20HW Power Strip offers 20 amp multi-outlet AC power distribution in a convenient 36 inch hardwire cabinet. Includes knockout panels to accept 3/4 in. conduit fittings for hardwire installation and 12 output receptacles with 2.99 inch center-to-center spacing. Ideal for horizontal or vertical raceway style power distribution in office, workbench, industrial, networking and telecom applications. INPUT/OUTPUT: Input: Hardwire access via knockout panels that accept 3/4 inch conduit fittings Output: 12 Outlets total (2 NEMA 5-15/20R and 10 NEMA 5-15R)

ELECTRICAL: 120V AC, 50/60Hz, 20A (no circuit breaker)

FORMAT: 36 inch strip format

#### **Features**

- · Versatile all-metal 36 inch format with outlets arranged in a single row
- Knockout panels for 3/4 inch conduit fittings allow permanent hardwire installation
- Ideal for horizontal or vertical raceway style power distribution in office, workbench, industrial, networking and telecom applications
- 12 outlets total: 2 NEMA 5-15/20R (20A) and 10 NEMA 5-15R (15A)
- 20 amp electrical capacity
- 120VAC, 50/60Hz electrical compatibility

# **Specifications**

OVERVIEW		
UPC Code	037332042385	
OUTPUT		
Frequency Compatibility	50 / 60 Hz	





Output (Watts)	2400
Output Receptacles	(2) 5-15/20R; (10) 5-15R
Transformer Accommodation	(6) Yes
Outlet Spacing	2.99 in.
Right-Angle Outlets	No
INPUT	
Nominal Input Voltage(s) Supported	120V AC
Recommended Electrical Service	20A 120V
Voltage Compatibility (VAC)	120
Input Plug Type	Hard-wire
Input Cord Length (ft.)	0
Input Cord Length (m)	0.00
Integrated Cord Clip	No
PHYSICAL	
Shipping Dimensions (hwd / in.)	2.50 x 2.60 x 41.00
Shipping Dimensions (hwd / cm)	6.35 x 6.60 x 104.14
Shipping Weight (lbs.)	3.65
Shipping Weight (kg)	1.66
Unit Dimensions (hwd / in.)	36 x 1.5 x 1.5
Unit Dimensions (hwd / cm)	91.44 x 3.8 x 3.8
Material of Construction	Metal
Integrated Keyhole Mounting Slots	No
Receptacle Color	Beige
Color	Beige
Outlets Measurement (Center to Center)	101.60mm
Anti-Microbial Protected	No
CERTIFICATIONS	
Canada	cUL
Approvals	UL
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty



**Tripp Lite**1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <a href="https://www.tripplite.com/products/product-certification-agencies">https://www.tripplite.com/products/product-certification-agencies</a>