



FACE VIEW



MALE FACE VIEW	
3-POLE	4-POLE
1 BROWN 3 BLUE 4 BLACK	1 BROWN 2 WHITE 3 BLUE 4 BLACK

POLE	MATERIAL NUMBER	ENGINEERING NUMBER	FINISHED LENGTH IN/MM
3	1200880042	503006A10M020	6.56' +3.50" -0 [2.0M +88.9 -0]
3	1200880044	503006A10M050	16.40' +6.50" -0 [5.0M +165.1 -0]
4	1200880059	504006A10M020	6.56' +3.50" -0 [2.0M +88.9 -0]

CONNECTOR SPECIFICATION:	
VOLTAGE RATING	3-4POL:60V/AC 75V/DC
AMPERAGE RATING	3 AMPS
PROTECTION	IP67
OPERATING TEMPERATURE	-20°C TO 105°C
UL CERTIFICATIONS	UL listed, File #E152210
CSA CERTIFICATIONS	CSA CERTIFIED, File LR6837

ITEM	COMPONENT	MATERIAL	FINISH
1	SLEEVE INSERT	PA	
2	CONTACT SOCKET	COPPER ALLOY	GOLD OVER NICKEL
3	SNAP SLEEVE	BRASS	NICKEL PLATED
4	OVERMOLD	TPE	YELLOW
5	CABLE- 24 AWG, (COPPER STRANDING) 3/4 CONDUCT. 300V	JACKET: PVC	YELLOW

DESCRIPTION EC NO: WEU2010-0300 DRWN: REISSNER 2010/01/25 CHKD: FP APPR: NSTAUDIG 2010/01/29	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED) mm INCH 4 PLACES ±--- ±--- 3 PLACES ±--- ±--- 2 PLACES ±--- ±.01 1 PLACE ±0.3 ±--- ANGULAR ± --- °	DIMENSION STYLE	SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION NC 3/4P M STR SNAP/SCREW 24AWG PVC CABLE MOLEX INCORPORATED SD-120088-005	
	= 0 = 0		IM/MM	2:1	METRIC		
	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SEE TABLE	DRAWN BY DATE REISSNER 2010/01/25 CHECKED BY DATE FP 2010/01/20 APPROVED BY DATE NSTAUDIG 2010/01/28	DOCUMENT NO. SD-120088-005		SHEET NO. 1
	SIZE A3		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION				