


TOLERANCE UNLESS OTHERWISE SPECIFIED .X ±0.25 .XX ±0.13


.XXX ±0.10

THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMBER **ORIGINAL**





NOTES:

MATERIAL:

HOUSING: THERMOPLASTIC POLYESTER, UL94V-0

637 ASSEMBLY

SHEET

DATE: AUG. 01/2018

OF

ISSUE

SHELL: STEEL, TIN PLATED

CONTACT: COPPER ALLOY, 30µ GOLD PLATED

SW REFERENCE NO.:

OPERATING TEMPERATURE: -55°C TO +85°C

CURRENT RATING: 3A PER CONTACT

CONTACT RESISTANCE: $25m\Omega$ MAX. **INSULATOR RESISTANCE:** 5000MΩ min.

DIELECTRIC

WITHOUT WRITTEN PERMISSION.

WITHSTANDING VOLTAGE: 1000V AC rms

637 SERIES D-SUB CONNECTOR DRAWN: CHECKED: THESE DRAWINGS AND SPECIFICATIONS SCALE: 1:1 THIS SERIES FULLY CONFORMS TO EDAC INC ARE THE PROPERTY OF EDAC INC..AND THE EUROPEAN UNION DIRECTIVES TORONTO, ONTARIO SHALL NOT BE REPRODUCED, OR COPIED 637-062-630-249 DRAWING NUMBER: OR USED AS THE BASIS FOR THE CANADA 2011/65/EU FOR RoHS COMPLIANCY. MANUFACTURE OR SALE OF APPARATUS YOUR CONNECTION TO QUALITY & SERVICE PART NUMBER: 637-062-630-249