

## RF TERMINATION

### Type 65010\_N-50-3/19-\_N

#### Description

Standard Termination, Medium Power



#### Product Configuration

Connector	N plug (male)
Interface standards	IEC 60169-16_MIL-STD-348A/304_CECC 22210

#### Technical Data

##### Electrical Data

Nominal Impedance	50 Ω		
Frequency range	0 to 18 GHz		
Frequency sub range	DC to 6 GHz	6 to 12.4 GHz	12.4 to 18 GHz
VSWR max.	1.2	1.3	1.4
Power rating	10 Watt average power up to 25 °C ambient temperature, linearly derated to 2 Watt at 125 °C ambient temperature. 250 Watt peak power , 5 μs pulse, 0.05 % duty cycle		

##### Mechanical Data

Weight	0.044 kg
--------	----------

##### Environmental Data

Operating temperature	-65 °C to 125 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

##### Material Data

Piece Part	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating
Outer contact	Stainless Steel	Passivated (Plating)
Body	Aluminium	Anodized
Insulator	PTFE (Polytetrafluoroethylene)	
Coupling nut	Stainless Steel	Passivated (Plating)

#### Related Documents

Outline drawing	DOU-00120643
-----------------	--------------

#### Ordering Information

Single Packaging	65010_N-50-3/19-_NE
Packaging	