т (О Т	m		0	Φ		
Keying Shore	wn as example		LAYOUT SHOW	YN AS EXAMPLE		
 CHARACTERISTICS -Standard : Based on ML-DTL-38999 Series III -Shell Material : Aluminium -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8µm minimum 	Connector dimensionDimNominalØS35.7 MaxZ31 MaxVV THREADM25x1-6g		the Specifications issued by e (professional recom	ucts which does not compli ither of the Parties or by a mendation, technical notice Country Jurisdictic	y with third party	
-Durability: 500 Mating cycles-Delivered without Souriau contacts-Temperature Range: -65°C to +200°C-Salt Spray: 48 hours		A 14-10-2016 I ISS DATE Designed By:		517F20PDL	USTOMER DRAWING	MOD N°
BASIC SERIES: 8D 5 - 17 F 20 P D SHELL TYPE : Plug with RFI Shielding	Delivered W/O Contacts ORIENTATION : D CONTACT TYPE : PIN(500 Matings)	SOURIAU	General Toleran ± WWW.SOURI	AU.COM	Series NPRDS / PROJECT 859 This document is the prope SOURIAU it must not be reproduce communicated without peri	ed or mission
PLATING : F = Nickel H G F	CONTACT LAYOUT : 17-20	FORMAT A3 D		IAU DRG N° 7F20PDL-C B	A	SHEET 1/2

	Ŧ	۵	<u>п</u>	m		0	
4	(Contact Layout 20* 4# 12 16#22D					
S	Ctc A B C D 1 2 3 4 5 6 7 8 9 10 10 11 12 13	X Y 0 5.51 3.17 0 0 -5.51 -3.17 0 4.16 7.06 4.29 4.29 7.11 4.03 8.05 1.4 8.05 -1.4 7.11 -4.03 4.29 -4.29 4.16 -7.06 -4.16 -7.06 -4.29 -4.29 -4.16 -7.06 -4.29 -4.29 -4.16 -7.06 -4.29 -4.29 -5.05 -1.4 -8.05 1.4 -8.05 1.4					ther nend Coun FR
	14 15 16	-7.11 4.03 -4.29 4.29 -4.16 7.06	F	E	A 14-10-20 ISS DATE Designed By: TITLE SCALE NA SOURIAN FORMAT A3 D	General li Tolerand ±	umi near ces:

