



Contact Layout



Contacts (Insert arrangement 21-11)						
Contact position ID	Location		Contact position ID	Location		
	X-axis (mm)	Y-axis (mm)		X-axis (mm)	Y-axis (mm)	
A	+121 (3.07)	+332 (8.43)	G	-348 (8.84)	-061 (1.55)	
B	+306 (7.77)	+177 (4.50)	H	-306 (7.77)	+177 (4.50)	
C	+348 (8.84)	-061 (1.55)	J	-121 (3.07)	+332 (8.43)	
D	+227 (5.77)	-270 (6.86)	K	+000 (0.00)	+123 (3.12)	
E	+000 (0.00)	-353 (8.97)	L	+000 (0.00)	-115 (2.92)	
F	-227 (5.77)	-270 (6.86)	---	---	---	

Shell size	Arrangement no.	Number of contacts	Size contacts	Service rating	Contact location	Supersedes
21	-11	11	12	I	All	MS20055-11

Panel cutout

JAM NUT RECEPTACLE (TYPE 7)



Max. thickness panel for receptacle: Type 7: 3.2 mm

Dim	Nominal
B	37.08+0/-0.25
ØC	38.35+0.25/-0

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

Country	Jurisdiction & Control List
FR	Not Listed

PN: 8D721W11PD

A	08-11-2016	First Release	
ISS	DATE	Latest modification - by	MOD N°
Designed By:		Date:	<b>CUSTOMER DRAWING</b>
<b>TITLE</b>	Aluminium Receptacle 8D series		
SCALE		General linear Tolerances:	NPRDS / PROJECT
NA		±--	<b>859</b>
<b>SOURIAU</b>	<b>WWW.SOURIAU.COM</b>		This document is the property of SOURIAU it must not be reproduced or communicated without permission
FORMAT	<b>SOURIAU DRG N° 8D721W11PD-C</b>		SHEET 2/2