T Q T	m		0	Ξ		
A Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z						4
CHARACTERISTICS	hown as example		LAYOUT SHO	WN AS EXAMPLE		3
 Standard : Based on MIL-DTL-38999 Series III Shell Material : Composite Shell Plating : Without Plating Insulator : Thermoplastic Contacts : Copper Alloy Seals & Grommet : Silicon Elastomer Contact Plating : Gold over copper Alloy 0.8µm minimum Durability : 500 Mating cycles Delivered with Souriau contacts and Accessories Temperature Range : -65°C to +175°C 	Connector dimensionDimNominalØS25 MaxZ31 MaxVV THREADM15x1-6g		the Specifications issued by (professional recor PN: 8 E	oducts which does not con either of the Parties or by mmendation, technical no	nply with y a third party	2
-Salt Spray : 2000 hours -Mass : 12.8 g ± 10%	.	A 18-10-2016 F ISS DATE Designed By: TITLE SCALE	Latest modification - by Date:	Composite Plug 8E	CUSTOMER DRAWING D series NPRDS / PROJECT	
→ BASIC SERIES: 8D 5 - 11 X 01 A SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11 PLATING : X = Without Plating	B ORIENTATION : CONTACT TYPE : PIN(500 Mating CONTACT LAYOUT : 11-0	: B gs) SOURIAU	WWW.SOUR	ances: IAU.COM RIAU DRG N°	859 This document is the property of SOURIAU it must not be reproduced or communicated without permission SHEET	1
H G F	E	D AS	C 8D5	511X01AB-C	A 1/2	

r	т	۵	г – – –	m		0	
		Contact Layout					
4		01					
		1 # 12 11-01	7				
ى	Ctc A	X Y 0 0					
	1						
	F					SOURIAU shall not be liable t due to a use of the Produ the Specifications issued by eit (professional recomm	icts wh ther of
N						PN: 8D5	Countr FR
					ISS DATE	6 First Release Latest modification - by	
					Designed By: TITLE SCALE		mpo
_					SOURIAL	General lin Toleranc ±	ces:
					FORMAT A3	SOURI 8D51	IAU
L	Н	G	F	E	D	C	

