	T Q T	m	D		0		Φ	A		-
4	R 22.6 Max (r) (r) (r) (r) (r) (r) (r) (r) (r) (r)	S				YOUT SHOWN AS EXAM	APLE			4
	Keying CHARACTERISTICS Standard : Based on MIL-DTL-38999 Series III	Shown as example Connector dimension Dim Nominal								
N	-Shell Material: Aluminium-Shell Plating: Black Zinc Nickel-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastomer-Contact Plating: Gold over copper Alloy 0.8µm minimum-Durability: 500 Mating cycles	A         34.9±0.3           B         19.07+0.1/-0.15           R         32.5Max           S         31.8±0.4           W         2.2+0.9/-0.1           VV THREAD         M15x1-6g			due to a use the Specifications (professi	not be liable for any no of the Products which s issued by either of the onal recommendation, Country FR	does not comply v e Parties or by a th technical notice.) Jurisdiction Not	with ird party		2
	-Delivered without Souriau contacts -Temperature Range : -65°C to +175°C -Salt Spray : 500 hours			A 01-10-20 ISS DATE	P 16 First Release Latest modification	N: 8D711Z02	2PBL		MOD N°	_
	-Mass : 17.18 g ± 10%			esigned By:	Date:	Aluminium Re		TOMER DRAWING		
	BASIC SERIES:8D7-11Z02PSHELL TYPE : Jam nut Receptacle	B L Delivered W/C ORIEN CONTACT TYPE : PIN(50	TATION : B	SCALE NA		General linear Tolerances: ±	M	PRDS / PROJECT 859 This document is the pro SOURIAU it must not be reproduc ommunicated without pe	ced or	1
	PLATING : Z = Black Zinc Nickel	CONTACT LAYO		FORMAT A3	С	SOURIAU D 8D711Z02F	RG N°	A	SHEET 1/2	

Г	D I	т п	D O	B	
4	Contact Layout		Panel cutout JAM NUT RECEPTACLE (TYPE 7)		4
	Contacts (Insert arrangement 11-2)         Contact position       Contact location (mm)         ID       X-axis       Y-axis         ID       (mm)       (mm)         A       +.095 (2.41)       +.000 (.00)         B      095 (2.41)       +.000 (.00)         Shell       Arrangement no.       Number of contacts       Size       Service rating       Contact location         11       -2       2       16       I       All		Dim         Nominal           B         19.59+0/-0.2	25	
ω			ØC 20.96+0.25/		3
			due to a use of the Proc the Specifications issued by	le for any non-conformity or damage ducts which does not comply with either of the Parties or by a third party mendation, technical notice.)	
D			A 01-10-2016 First Release	FR     Not Listed       711Z02PBL	2
				CUSTOMER DRAWING	J°
_ <b>_</b>			SCALE NA SOURIAU SOURIAU SOURIAU	IAU.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission	1
				RIAU DRG N°SHEET11Z02PBL-C2/2	
L	H G	F	DC	BA	