ATGBICS QSFP-100G-CWDM4-S Cisco Compatible Transceiver QSFP28 100GBase-CWDM4 (1310nm, SMF, 2km, LC, DOM)

Brand : ATGBICS

Product code: QSFP-100G-CWDM4-S-C

Product name : QSFP-100G-CWDM4-S Cisco Compatible Transceiver QSFP28 100GBase-CWDM4 (1310nm, SMF, 2km, LC, DOM)

QSFP-100G-CWDM4-S Cisco Compatible Transceiver QSFP28 100GBase-CWDM4 (1310nm, SMF, 2km, LC, DOM)


ATGBICS QSFP-100G-CWDM4-S Cisco Compatible Transceiver QSFP28 100GBase-CWDM4 (1310nm, SMF, 2km, LC, DOM):

ATGBICS QSFP-100G-CWDM4-S 100GBase-CWDM4 QSFP28 supports a distance of up to 2km over singlemode fibre (SMF) using four wavelengths of 1271, 1291, 1311 and 1331nm via an LC connector. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product meets the specification of Cisco QSFP-100G-CWDM4-S= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.





Performance		Features	
SFP transceiver type *Fiber opticMaximum data transfer rate *100000 Mbit/sInterface type *QSFP28Single-mode fiber (SMF) supportedMulti-mode fiber (MMF) supportedFiber optic connectorLCSFP transceiver standardCWDM4Maximum transfer distance2000 mWavelength1310 nmEthernet LANEthernet interface type100 Gigabit EthernetDigital Diagnostics Monitoring (VDM)Wavelength-division multiplexing (WDM)	100000 Mbit/s QSFP28 ✓ K LC	Certification	CE, FCC, RoHS
		Power	
		Input voltage Maximum voltage Power consumption (typical)	3.3 V 3.5 V 1 W
		Operational conditions	
	2000 m 1310 nm ✓ 100 Gigabit Ethernet	Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Weight & dimensions Width Depth	70 °C 0 - 70 °C -40 - 85 °C 0 - 95% 0 - 95% 13.5 mm 72.4 mm
Product colour	Silver	Height Weight	18.4 mm 42 g
Housing material Plug and Play	Metal V	Packaging data	
Hot-Plug support Hot-swap	to install	Number of products included Package type	1 pc(s) Box
Easy to install		Technical details	
ountry of origin United Kingdom rand compatibility Cisco	Sustainability compliance Sustainability certificates Doesn't contain	✔ RoHS Lead	



5056468717153

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.