

6

5


4

3



2

1

MALE FACE VIEW



- 1 GRAY
- 2 BROWN
- 3 BLUE
- 4 BLACK



ⓓ F0P4006K18M010

Wire type
14/4C AWG
BLACK TPE

cable length
M005 = 0.5 Meter
M010 = 1 Meter
M100 = 10 Meter

MECHANICAL
CONTACT: GOLD/NICKEL OVER COPPER ALLOY
INSERT: BLACK NYLON
COUPLING NUT: NICKEL PLATED BRASS
MOLDED BODY: BLACK ARNITEL
CABLE: 14 AWG 4 CONDUCTORS BLACK TPE JACKET

CABLE MARKING: Exxxxxx 14AWG 4/C (UL) TYPE TC-ER 90C DRY
600V OR AWM 90C 600V - - - cRu AWM I/II A/B 90C 600V FT4

ELECTRICAL
VOLTAGE RATING: 300V AC/DC
AMPERAGE: 16A

ENVIRONMENTAL
PROTECTION: IP67

OPERATING TEMP: -20°C TO 90°C

UPDATE MATRIX NO. & OVRMLD EC NO: IPC2017-0883 DRWN: MZIELINS 2017/03/20 CHKD: TWOLDEGE2017/03/22 APPR: BWOODMAN 2013/12/17	QUALITY SYMBOLS	DESCRIPTION REV
	$\nabla=0$ $\sphericalangle=0$	
	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	
	SIZE A	

GENERAL TOLERANCES (UNLESS SPECIFIED)		
	mm	INCH
4 PLACES	±---	±---
3 PLACES	±---	±.005
2 PLACES	±.13	±.010
1 PLACE	±.25	±.020
ANGULAR ±.5°		

DIMENSION STYLE	
MM/INCH	
DRAWN BY	DATE
TWOLDEGE	2013/04/24
CHECKED BY	DATE
BRUPERT	---
APPROVED BY	DATE
BWOODMAN	2013/12/17
MATERIAL NO.	

SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION
1:1	INCH	
TITLE		
M12-POWER ASSEMBLY 4-POLE MALE F-CODE ST. 14/4C AWG BLACK TPE		
MOLEX INCORPORATED		
DOCUMENT NO.		SHEET NO.
SD-120500-001		1 OF 1
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		

6

5

4

3

2

1

E

E

D

D

C

C

B

B

A

A