

TOLERANCE UNLESS OTHERWISE SPECIFIED DO NOT MAKE MANUAL REVISIONS TO MASTER.




ISSUE NUMBER	
ORIGINAL	

(1)







NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

OPERATING TEMPERATURE:

.X ±0.25 .XX ±0.13 .XXX ±0.05

POWER/CO-AX CONTACT RATING:10A (CURRENT)(IF PRESENT)SIGNAL CONTACT CURRENT RATING:5A PER CONTACTSIGNAL CONTACT RESISTANCE:10mΩ MAX.

INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE: 5000MΩ min.


-55°C ~ 125°C

1000V AC rms

THERMOPLASTIC POLYESTER, UL94V-0

COPPER ALLOY, 30µ" GOLD PLATED

STEEL, NICKEL PLATED



	COMBINATION D-SUB		OMBO ASSEMBLY			
COMBINATION			COMBINATION D-SUB		DATE: JAN. 01/20	19
			DATE:			
	ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2		
CANADA		DRAWING NUMBER: 629-2W2-	640-1NE	ISSUE		
		PART NUMBER: 629-2W2-	640-1NE	1		



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

