т (О) т (П) т П	
	4
	LAYOUT SHOWN AS EXAMPLE 3
Keying Shown as example	
CHARACTERISTICS Connector dimension -Standard : Based on MIL-DTL-38999 Series III Dim Nom	
-Shell Material : Aluminium ØS 29.4 -Shell Plating : Black Zinc Nickel Z 31 M -Insulator : Thermoplastic VV THREAD M189 -Contacts : Copper Alloy - -Seals & Grommet : Silicon Elastomer - -Contact Plating : Gold over copper Alloy 0.8μm minimum	SOURIAU shall not be liable for any non-conformity or damage
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories	PN: 8D513Z03SE
-Temperature Range -65°C to +175°C	A 19-10-2016 First Release
-Salt Spray : 500 hours	ISS DATE Latest modification - by MOD N°
	Designed By: Date: CUSTOMER DRAWING
	TITLE Aluminium Plug 8D series
BASIC SERIES: 8D 5 - 13 Z 03 S E SHELL TYPE : Plug with RFI Shielding	SCALE General linear NPRDS / PROJECT NA Tolerances: 859
CONTACT TYPE : Standard Crimp Contact	ORIENTATION : E SOURIAU This document is the property of SOURIAU. It must not be reproduced or it must not be reproduced or
SHELL SIZE : 13 CONTACT TYPE : S	
PLATING : Z = Black Zinc Nickel CONT	LAYOUT : 13-03 FORMAT SOURIAU DRG N° SHEET A3 8D513Z03SE-C 1/2

	Т	۵	нт – П	m	D	0	
		Contact Layout					
4		03					
		3#16 13-03					
	Ctc A B C	X Y 2.39 1.47 0 -2.79 -2.39 1.47					
ယ							
	1						
						SOURIAU shall not be liab due to a use of the Pro the Specifications issued by (professional recon	ducts v either
N							Cour FF
						PN: 80)513
						2016 First Release	
					ISS DA Designed By:	TE Latest modification - by Date:	
					TITLE	A	Alumi
<u> </u>					SCALE NA	Genera Tolera	
					SOURI		
				_	FORMAT A3	SOU 8D5	RIA 513

G

Н

F

Е

D

С

