

## ATGBICS Dell DAC-Q28-4SFP28-25G-5M Compatible 100G QSFP28 to 4x25G SFP28 Passive Direct Attach Copper Breakout Cable 5m **Passive**

**Brand:** ATGBICS

Product code: DAC-Q28-4SFP28-25G-5M-C

Product name: Dell DAC-Q28-4SFP28-25G-5M Compatible 100G QSFP28 to 4x25G SFP28 Passive Direct Attach Copper

Breakout Cable 5m Passive

Dell DAC-Q28-4SFP28-25G-5M Compatible 100G QSFP28 to 4x25G SFP28 Passive Direct Attach Copper Breakout Cable 5m Passive

ATGBICS Dell DAC-Q28-4SFP28-25G-5M Compatible 100G QSFP28 to 4x25G SFP28 Passive Direct Attach Copper Breakout Cable 5m Passive:

ATGBICS DAC-Q28-4SFP28-25G-5M compatible 100GBase QSFP28 to 4x25G SFP28 direct attach breakout cable operates over passive copper with a cable length of 5m. It is suitable for very short distances and provides a cost-efficient way to connect hardware within close proximity racks. This breakout cable connects to 1 x 100G QSFP+ port of a switch on one end and to 4 x 25G SFP+ ports of a switch on the other end. Our product is built to the exact specification of Dell DAC-Q28-4SFP28-25G-5M= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards and protocols including; IEEE802.3bj, InfiniBand EDR, MSA SFF-8665 & SFF-8402.







Features		Features	
Product colour * Cable length *	sile length * 5 m sinector 1 * QSFP28 sinector 2 * 4x SFP+ sinector 1 gender * Male sinector 2 gender * Male site material Polyvinyl chloride (PVC) ductor material Copper sernet interface type 100 Gigabit Ethernet	Plug and Play Certification	<b>√</b> CE,FCC
Connector 1 *		Operational conditions	
Connector 1 gender * Connector 2 gender * Jacket material Conductor material		Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	0 - 70 °C -40 - 80 °C 10 - 90% 10 - 85%
Ethernet interface type		Packaging data	
Networking standards		Quantity per pack	1 pc(s)
AWG wire size	30	Technical details	
Data transfer rate 100000 I	100000 Mbit/s	Sustainability certificates	RoHS



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.