





| ISSUE NUMBER |     |
|--------------|-----|
| ORIGINAL     | (1) |





NOTES:


MATERIAL: HOUSING: SHELL: CONTACT:

DIELECTRIC

**OPERATING TEMPERATURE:** 

WITHSTANDING VOLTAGE:

THERMOPLASTIC POLYESTER, UL94V-0 STEEL, NICKEL PLATED COPPER ALLOY, 30µ" GOLD PLATED




20A (CURRENT) POWER/CO-AX CONTACT RATING: (IF PRESENT) SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT SIGNAL CONTACT RESISTANCE:  $10m\Omega$  MAX. INSULATOR RESISTANCE: 5000MΩ min.

.XX ±0.13 .XXX ±0.05

1000V AC rms

-55°C ~ 125°C



|  | COMBINATION D-SUB                    |   | SW REFERENCE NO.: 629 COMBO ASSEMBLY |                  |       |
|--|--------------------------------------|---|--------------------------------------|------------------|-------|
|  |                                      |   | DRAWN: C.B                           | DATE: JAN. 01/20 | 19    |
|  |                                      |   | CHECKED:                             | DATE:            |       |
|  | EDAC INC                             | THESE DRAWINGS AND SPECIFICATIONS<br>ARE THE PROPERTY OF EDAC INC.,AND  | SCALE: (IN C.A.D. 1:1)               | SHEET 1 OF       | 2     |
|  | TORONTO, ONTARIO<br>CANADA           | SHALL NOT BE REPRODUCED, OR COPIED<br>OR USED AS THE BASIS FOR THE<br>MANUFACTURE OR SALE OF APPARATUS<br>WITHOUT WRITTEN PERMISSION. | DRAWING NUMBER: 629-21W1650-2N1      |                  | ISSUE |
|  | YOUR CONNECTION TO QUALITY & SERVICE |   | PART NUMBER: 629-21W <sup>2</sup>    | 1650-2N1         | 1     |



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

