

エ 1	Q	П	m In the second se		0
			-	_	







Keying Shown as exar

F

CHARACTERISTICS

ω

7

-Standard : Based on MIL-DTL-38999 Series III

CONTACT TYPE : Standard Crimp Contact

SHELL SIZE : 13

PLATING : F = Nickel

Н

\square	-Shell Material	: Aluminium								
		pp								
	-Shell Plating	: Nickel R1								
	-Insulator	: Thermoplastic R2								
	-Contacts	: Copper Alloy	+-							
	-Seals & Grommet	: Silicon Elastomer W	+							
N	-Contact Plating	: Gold over copper Alloy 0.8µm minimum Z								
	-Durability	: 500 Mating cycles VV THREAD								
	-Delivered without Souriau contacts									
	-Delivered without Sol	unau contacts								
	-Temperature Range	- 65°C to +200°C								
	-Salt Spray	: 48 hours								
	-Mass	: 17.41 g ± 10%								
	BASIC SERIES:	8D 0 - 13 F 26 S B L								
_	SHELL TYPE : Square	Flange Receptacle								

G

Dim Nominal P 3.25±0.2 PP 4.93±0.2 R1 23.01 R2 20.62 S 28.6±0.3	
PP 4.93±0.2 R1 23.01 R2 20.62	
R1 23.01 R2 20.62	
R2 20.62	
S 28.6±0.3	
V 20.83+0/-1.25	5
W 2.1/2.5	
Z 31.5 Max	
VV THREAD M18x1-6g	

т		D		0		σ	>	•	
	1				YOUT SHOWN AS	EXAMPLE			4
Connector dimension Dim Nominal P 3.25±0.2 PP 4.93±0.2 R1 23.01 R2 20.62 S 28.6±0.3 V 20.83+0/-1.25 W 2.1/2.5 Z 31.5 Max V THREAD M18x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.) Country Jurisdiction & Control List FR Not Listed							2
		A 14	-10-2016	First Release	PN: 8D013	F26SBL			
-		ISS Designed By	DATE /:	Latest modificatio Date:			MOD N°	_	
Delivered V	V/O Contacts	TIT SCALE NA			General linear Tolerances: ±	Im Receptacl	NPRDS / PROJECT 859		1
			OURIAU This document is the property of SOURIAU it must not be reproduced or communicated without permission			duced or permission			
CONTACT LA	YOUT : 13-26	FORMAT A3				U DRG N° 26SBL-C		SHEET 1/2	
E		D		С		В	I A	L	

-	T	۵	н г	m	D	0
		Contact Layout				Panel Cutou
4	(26			2 -	SQUARE FLANGE RECEPTACLE (TYPE 0) REAR MOUNTING
_		6#22D			y	
ω	Ctc A B C D E F 1 2	13-26 X Y 0 3.47 2.47 4.34 2.47 -4.34 0 -3.47 -2.47 -4.34 -2.47 4.34 3.25 0 -3.25 0				Dim ØA ØA R1 ØT
	F					SOURIAU shall not be liable for any
						due to a use of the Products wh the Specifications issued by either of (professional recommendat
N						Countr FR
						PN: 8D013F
					A 14-10-20 ISS DATE	16 First Release Latest modification - by
					Designed By:	Date: Aluminium
_ _					SCALE NA	General linear Tolerances:
					SOURIA	U WWW.SOURIAU.C
				_	FORMAT A3	SOURIAU 8D013F2
L	Н	G	F	E	D	C

