

Specification Sheet

Part Number: 553-50225



ShrinkTrak Labels, 1-Sided, Unslit, Halogen Free, 1.5" (38.1mm), PO-X, Yellow, 150/box

Article Number

553-50225

Type

HFST39-13YE

Color

Yellow (YE)

Features & Benefits

- Slide Slit and optional center slits for easy wire insertion.
- Smooth surface for clean and legible printing.
- Supplied on a ladder style carrier so that markers can be kitted after printing.
- A 3:1 shrink ratio means fewer skews as each marker covers a wider range of wire diameters.

Quantity Per

box

Product Description

HellermannTyton's ShrinkTrak heat shrinkable markers make it easy to mark wire, cable and other components. The military approved heat shrink tubing is flattened and assembled in a ladder style carrier system for easy printing using a thermal transfer printer. The ladder system creates a kit of markers that can be sorted, removed and applied in any order thus saving time, labor and speeding production.

Short Description

ShrinkTrak Labels, 1-Sided, Unslit, Halogen Free, 1.5" (38.1mm), PO-X, Yellow, 150/box

Global Part Name

HFST39-13YE-PO-X-YE

Variant

Thin-Wall

Width W (Imperial)

1.9

Width W (Metric)

48.26

Thickness T (Imperial)

.003

Thickness T (Metric)

.0762

Height H (Imperial)

2.26

Height H (Metric)

57.4

Width of Liner (Metric)

76.2

Width of Liner (imperial)

3.0

Outside Diameter OD(Imperial)

1.5

Outside Diameter OD(metric)

38.1

Outside Diameter Max(Imperial)

1.5

Outside Diameter Max (metric)

38.1

Wall Thickness WT (Imperial)

0.04

Wall Thickness WT (Metric)

1.01

Material

Polyolefin, cross-linked (PO-X)

Material Shortcut

PO-X

US MIL SPEC

SAE-AMS-DTL-23053/5 Class 1 and 3

MIL-STD-202G Method 215K
SAE-AS81531

Flammability

UL 224 VW-1

Halogen free

Yes

Operating Temperature (Metric)

-67°F to +275°F (-55°C to +135°C)

Reach Complaint(Article 33)

Yes

ROHS Complaint

Yes

Certification/Specification WEB

SAE - AMS - DTL-23053/5 Class 1 and 3 UL 224 125 °C 600V VW-1 SAE - AS81531

Package Quantity(Imperial)

150

Package Quantity (Metric)

150

Customs Number

3917320000

Labels per Column 1

Labels per Row 1

Weight (Metric) 0.68

Weight (Imperial) 1.48