


0 0 0 0 0 0




THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



ORIGINAL 1





NOTES:

MATERIAL:

HOUSING: THERMOPLASTIC POLYESTER, UL94V-0

SHELL: STEEL, NICKEL PLATED

CONTACT: COPPER ALLOY, 30µ GOLD PLATED

OPERATING TEMPERATURE: -55°C TO +85°C

CURRENT RATING: 3A PER CONTACT

CONTACT RESISTANCE:  $25m\Omega$  MAX. INSULATOR RESISTANCE:  $5000M\Omega$  min.

**DIELECTRIC** 

WITHSTANDING VOLTAGE: 1000V AC rms

## 637 ASSEMBLY SW REFERENCE NO.: 637 SERIES D-SUB CONNECTOR DRAWN: C.B DATE: AUG. 01/2018 CHECKED: THESE DRAWINGS AND SPECIFICATIONS OF SCALE: 1:1 SHEET THIS SERIES FULLY CONFORMS TO EDAC INC ARE THE PROPERTY OF EDAC INC..AND THE EUROPEAN UNION DIRECTIVES TORONTO, ONTARIO SHALL NOT BE REPRODUCED, OR COPIED 637-044-630-041 ISSUE DRAWING NUMBER: OR USED AS THE BASIS FOR THE CANADA 2011/65/EU FOR RoHS COMPLIANCY. MANUFACTURE OR SALE OF APPARATUS YOUR CONNECTION TO QUALITY & SERVICE PART NUMBER: 637-044-630-041 WITHOUT WRITTEN PERMISSION.