# TRIPP-LITE

### Single-Gang UK-Style Gang Frame for Insert Modules, White

#### MODEL NUMBER: N042U-WF1-2





#### Highlights

- Ideal for home theater, VoIP or Ethernet in-wall wiring installations
- Helps prevent accidental cable damage and hides unattractive wiring
- Compatible with select Tripp Lite N042U-Series modules and inserts (sold separately)
- High-impact plastic construction designed to blend in with your home/office décor

#### Package Includes

N042U-WF1-2 Single-Gang UK-Style Gang Frame, White

British-style gang frame accepts compatible wall-mount insert for terminating premise audio/video, voice or data applications.

#### Features

#### U.K. Gang Frame Connects Your In-Wall Audio/Video, Voice or Data Cable Line

This gang frame for unloaded insert modules is ideal for terminating your premise wiring applications, including home theater, VoIP phones and Ethernet. The UK-style N042U-WF1-2 also protects electrical and network cables to help prevent accidental damage to your application. It's compatible with Tripp Lite's N042U-Series unloaded shuttered modules and inserts (sold separately).

#### High-Impact Construction Designed to Blend In Seamlessly with Your Room

This white plastic cover plate measures 86 x 86 millimeters (outer frame) and accepts one 50 x 50 millimeter module. It blends elegantly into any home or office décor for a sleek, professional installation. The ABS plastic construction meets UL 94V-0 flame-retardant standards for protection against fire and high heat.

## **Specifications**

OVERVIEW		
UPC Code	037332269478	
Accessory Type	Wall Plate	
Technology	Cat5/5e; Cat6; Cat6a; DisplayPort; HDBaseT; HDMI; USB	
Country/Region	UK	
PHYSICAL		
Color	White	
Material of Construction	ABS	



1000 Eaton Boulevard Cleveland, OH 44122 United States

(	
Total Number of Ports	1
Unit Dimensions (hwd / in.)	3.380 x 3.380 x 0.380
ENVIRONMENTAL	
Operating Temperature Range	14° to 140°F (-10° to 60°C)
Storage Temperature Range	-40° to 154°F (-40° to 68°C)
Operating Humidity Range	10% to 90% RH, (Non-Condensing)
Storage Humidity Range	10% to 90% RH, (Non-Condensing)
CONNECTIONS	
Number of Ports	1
Side A - Connector 1	KEYSTONE JACK CUTOUT
FEATURES & SPECIFICATIONS	
Antibacterial	No
STANDARDS & COMPLIANCE	
Product Certifications	UL 94; UL Listed; cUL Listed
Product Compliance	RoHS; REACH; Trade Agreements Act (TAA)
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	Lifetime limited warranty



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.