

Monitor - BL FPM 21.5 - 2400515

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



IP65-rated, 21.5-inch, flat panel LCD monitor with projected capacitive touch screen

Product Description

The Baseline BL FPM 21.5 is an industrial flat-panel monitor that can be used in applications where a remote display location is required.

Why buy this product

- 21.5-inch display
- DisplayPort 1.2, VGA, and DVI-I input ports
- Integrated configuration buttons
- Ambient operating temperatures from -10°C to 60°C
- 21.5-inch touch screen display

Key Commercial Data

Packing unit	1 STK
Weight per Piece (excluding packing)	1.000 g
Custom tariff number	85299020
Country of origin	Taiwan

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Display

Display	54.6 cm / 21.5"-TFT
Screen resolution	1920 x 1080 Pixel(s) (Full HD)
Backlighting	LED
Display backlight MTBF	> 50000 h
Touch technology	Projective-capacitive, ten-touch control
Colors	16.7 million colors

Monitor data

Monitor - BL FPM 21.5 - 2400515

Technical data

Monitor data

Network	Without network
Interfaces	1x USB 1.1, Typ A 1x USB 2.0, Typ A
Monitor output	1x DisplayPort 1x DVI-I 1x VGA
Slots	without slots
Optical drive	Without drive

General

Mounting type	VESA MIS-D, 100 Front installation
Weight	7.87 kg

Ambient conditions

Degree of protection	IP65 (front), IP20 (back)
Ambient temperature (operation)	-10 °C ... 60 °C
Ambient temperature (storage/transport)	-20 °C ... 75 °C
Permissible humidity (operation)	10 % ... 90 % (non-condensing)
Vibration (operation)	1g
Shock	15g, 11 ms impulse

Device supply

Supply voltage	24 V DC (typical)
Supply voltage range	12 V DC ... 24 V DC
Power supply unit	24 V DC

Standards and Regulations

Shock	15g, 11 ms impulse
Vibration (operation)	1g

Classifications

eCl@ss

eCl@ss 5.1	27242402
eCl@ss 6.0	19200201
eCl@ss 8.0	19200403

ETIM

ETIM 3.0	EC001425
----------	----------

Monitor - BL FPM 21.5 - 2400515

Classifications

ETIM

ETIM 4.0	EC001428
ETIM 5.0	EC001428

UNSPSC

UNSPSC 12.01	43211902
--------------	----------

Approvals


Approvals

Approvals

UL Listed / cUL Listed / cULus Listed

Ex Approvals

Approval details

UL Listed  <http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm> FILE E 238705

cUL Listed  <http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm> FILE E 238705

cULus Listed 