


C410C330J5G5TA

General Information

AxiMax 400 Comm COG, Ceramic, 33 pF, 5%, 50 VDC, COG, AxiMax, Commercial Standard



Series AxiMax 400 Comm COG

Description AxiMax, Commercial Standard

RoHS Yes

Termination Tin

AEC-Q200 No

Halogen Free Yes

Click here for the 3D model.

Dimensions	,
D	2.41mm MAX
L	4.32mm MAX
LL	25.4mm MIN
F	0.51mm +0.025/-0.076mm

Declaring Charifications				
Packaging Specifications				
Packaging	Bulk, Bag			
Packaging Quantity	300			

Specifications			
Capacitance	33 pF		
Measurement Condition	1 MHz 1.0Vrms		
Capacitance Tolerance	5%		
Voltage DC	50 VDC		
Dielectric Withstanding Voltage	125 VDC		
Temperature Range	-55/+125°C		
Temperature Coefficient	COG		
Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC)	30PPM/C, 1MHz 1.0Vrms		
Dissipation Factor	0.1% 1 MHz 1.0Vrms		
Aging Rate	0% Loss/Decade Hour		
Insulation Resistance	100 GOhms		

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.