

SCSI/Fibre Channel - 3-ft. SCSI Cable HD50M to HD50M Double Shielded

MODEL NUMBER: \$366-003



Highlights

- Premium double-shielded cable
- 25 twisted-pair conductors

System Requirements

 Any external SCSI II device or controller card requiring HD50 interface

Package Includes

 3ft SCSI Cable HD50M to HD50M Double Shielded

Description

Multi-platform SCSI II external peripheral cable HD50M/M. This 3ft cable is designed to connect two SCSI II (fast SCSI) devices together. Manufactured using double shielded 25 twisted pair high impedance cable. Constructed with low-capacitance, impedance matched, 28 AWG, stranded, tinned copper cable with insulated in polypropylene. Tripp Lite warrants this product to be free from defects in materials and workmanship for life.

Features

- Backwards compatibility with previous SCSI generations
- Double shielded (foil and braid)
- 25 twisted pair conductors
- · Low-capacitance impedance matched 28 AWG stranded tinned copper insulated in polypropylene
- All Tripp Lite SCSI products, regardless of the SCSI generation, meet the latest specifications of ANSI
- Tripp Lite offers a complete line of internal and external solutions for SCSI/RAID and fibre channel ranging from the very latest Ultra 320 to legacy SCSI-1 and every combination in between
- Tripp Lite warrants this product to be free from defects in materials and workmanship for life

Specifications

OVERVIEW	
UPC Code	037332014061
INPUT	
Cable Length (ft.)	3
Cable Length (m)	0.91





PHYSICAL		
Shipping Dimensions (hwd / in.)	11.75 x 7.00 x 0.50	
Shipping Dimensions (hwd / cm)	29.84 x 17.78 x 1.27	
Shipping Weight (lbs.)	0.48	
Shipping Weight (kg)	0.22	
CONNECTIONS		
Side A - Connector 1	HD50 (MALE)	
Side B - Connector 1	HD50 (MALE)	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies