

Specification Sheet

Part Number: 151-01051



The 90-degree configuration of this mini channel creates a solution for routing a wire harness around a corner.

Design allows the mini channel to be used with a wide range of panel thicknesses and hole diameters.

Mini Channel, 1.38" Long, 90° Angle, Fir Tree FT6B, PA66HIRHSUV, Black, 4000/box

Article Number 151-01051

Type BC90FT6B

Color Black (BK)

Quantity Per bag

Product Description HellermannTyton's Bundling Clips create a solution that allows the harness to be routed around a corner and fixated into the panel at this location.

Short Description Mini Channel, 1.38" Long, 90° Angle, Fir Tree FT6B, PA66HIRHSUV, Black, 4000/box

Global Part Name BC90FT6B-PA66HIRHSUV-BK

| | |
|--|--------------|
| Length L (Imperial) | 0.98 |
| Length L (Metric) | 25.0 |
| Fixation Method | Fir Tree |
| Width W (Imperial) | 0.06 |
| Width W (Metric) | 1.5 |
| Height H (Imperial) | 0.96 |
| Height H (Metric) | 24.5 |
| Panel Thickness Min (Imperial) | 0.02 |
| Panel Thickness Max (Imperial) | 0.22 |
| Panel Thickness Min (Metric) | 0.6 |
| Panel Thickness Max (Metric) | 5.5 |
| Mounting Hole Diameter D (Imperial) | 0.24 - 0.27 |
| Mounting Hole Diameter D (Metric) | 6.1 - 6.9 mm |
| Mounting Hole Diameter D Min (Imperial) | 0.24 |
| Mounting Hole Diameter D Max (Imperial) | 0.27 |
| Mounting Hole Diameter D Max (Metric) | 6.9 |

| | |
|-------------------------------------|--|
| Material | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| Material Shortcut | PA66HIRHSUV |
| Flammability | UL 94 HB |
| Operating Temperature | -40°F to +221°F (-40°C to +105°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 4000 |
| Package Quantity (Metric) | 4000 |
| Customs Number | 3926909988 |