		T Q T M					
CHARACTERISTICS Standard: Based on MIL DT: 38995 Series III Shell Naterial ::::::::::::::::::::::::::::::::::::	4			4			
CHARACTERISTICS Standard: Based on MIL-DTL-38999 Series III Schell Material:	ω		LAYOUT SHOWN AS EXAMPLE	3			
CHARACTERISTICS Standard: Based on MIL-DTL-38999 Series III Schell Material:		Koving Chown as overalle					
-Standard : Based on MIL-DTL-3899 Series III Dim Dim Nominal Dim Nominal Dim Dim Nominal Dim Dim Nominal Dim Dim Nominal Dim							
Shell Material : Aluminium Shell Material : Aluminium Shell Plating : Nickel -Insulator :: Thermoplastic -Contacts :: Copper Alloy -Seals & frommet :: Slicon Elastomer -Contact Plating :: Gold over copper Alloy 0.3µm minimum -Durability :: Sourcast and Accessories -Delivered with Souriau contacts and Accessories - -Temperature Range :: - 65°C to +200°C -sait Spray :: 48 hours -Mass : 29.52 g + 10% BASIC SERIES: 8D 5 Shell MRFi Shielding : - CONTACT TYPE : Standard Crimp Contact 17 F 99 A C ORIENTATION :: C : - 17 SOURIAU WWW.SOURIAU cond : - NMID S/ PROJECT : - - Sourcau : - 17 F 99 A C - ORIENTATION :: C : - : - : - : - - - - - - - - 10 <td< td=""><td></td><td>Connector dimension</td><td></td><td></td></td<>		Connector dimension					
No -Contact Plating ::::::::::::::::::::::::::::::::::::		Shell Material : Aluminium Shell Material : Aluminium Shell Plating : Nickel Insulator : Thermoplastic Insulator : Thermoplastic					
-Durability : 500 Mating cycles -Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories -Temperature Range : -65°C to +200°C -Salt Spray : 48 hours -Mass : 29.52 g ± 10% Mass : 29.52 g ± 10% Mass : 29.52 g ± 10% Mod N* Mod N* Designed By: Date: CUSTOMER DRAWING TITLE Aluminium Plug 8D series SKIELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact ORIENTATION : C CORIENTATION : C				2			
-Salt Spray : 48 hours -Mass : 29.52 g ± 10% BASIC SERIES: 8D BASIC SERIES: 8D SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact ORIENTATION : C SOURIAU WWW.SOURIAU.COM SOURIAU		ability : 500 Mating cycles					
-Salt Spray : 48 hours -Mass : 29.52 g ± 10% -Mass : 29.52 g ± 10% BASIC SERIES: 8D 5 - 17 F 99 A C CONTACT TYPE : Standard Crimp Contact - 17 F 99 A C CONTACT TYPE - 17 F 99 A C C F F F F F F F F F F F F F F F F F F F			A 14-10-2016 First Release				
BASIC SERIES: 8D 5 - 17 F 99 A C SCALE SCALE SCALE SCALE SCALE SEGURIAL Basic Series: 859 859 1 1 1 SCALE SCAL			ISS DATE Latest modification - by MOD N°				
AND SERIES. BASIC SERIES. BASIC SERIES. Tolerances: Tolerances: 859 1 SHELL TYPE : Shelding Image: Standard Crimp Contact Image: Standard Crimp Contact NA Image: Standard Crimp Contact This document is the property of SOURIAU SOURIAU Image: Standard Crimp Contact Image:							
CONTACT TYPE Standard Crimp Contact SOURIAU SOURIAU ORIENTATION : C SOURIAU SOURIAU SOURIAU			Tolerances: 859	1			
		CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 17 CONTACT TYPE : PIN(500 Ma	SOURIAU SOURIAU SOURIAU It must not be reproduced or it must not be reproduced or it must not be reproduced or				
PLATING : F = Nickel FORMAT SOURIAU DRG N° SHEET		PLATING : F = Nickel CONTACT LAYOUT :	FORMAT SOURIAU DRG N° SHEET				
A3 8D517F99AC-C 1/2 H G F E D C B A		H G F E	5551715577C C				

r	Ŧ	۵	н г	m		0
		Contact Layout				
4	-x	$\begin{array}{c} +Y \\ R \oplus A \oplus B \oplus C \\ P \oplus S \oplus \Phi T \oplus D \oplus E \\ W \oplus \Phi^{2} - C Z \oplus U \oplus E \\ W \oplus \Phi^{2} - C Z \oplus U \oplus E \\ W \oplus \Phi^{2} - C W \oplus \Phi^{2} \\ W \oplus C \oplus U \oplus \Phi^{2} \\ W \oplus C \oplus U \oplus \Phi^{2} \\ W \oplus C \oplus U \oplus \Phi^{2} \\ -Y \end{array}$				
	B + 131 (3.3) C + 239 (6.07) D 306 (7.75) E + 319 (8.10) F + 2.78 (7.06) G + 189 (4.80) H + 0.67 (1.70) J - 0.67 (1.70) K 189 (4.80) L 278 (7.26)	Contacts Contact Iocation Y-axis Y-axis (mm) (mm) (mm) y2axis (mm) (mm) (mm) (mm) (mm) y2axis (y-axis) (y-axis)				
ω	17 00	mber of ntacts Size contacts Service rating Contact position ID Supersedes 2 16 I W,Z MS20053-99 21 20 I All others MS20053-99				
	F					
						SOURIAU shall not be liable for an due to a use of the Products w the Specifications issued by either o (professional recommenda
N						Count FR
					A 14-10-20	PN: 8D517
					ISS DATE Designed By:	Latest modification - by Date:
					TITLE	Alumir
→					SCALE NA	General linear Tolerances:
					SOURIA	U WWW.SOURIAU.C
					FORMAT A3	SOURIAU 8D517F
L	Н	G	F	E	D	C

