ASSOCIATION CONNECT	© Copyright 2005. IP	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.				This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lower level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.										
752-21.1		IPC Web Site for Information on IPC-1752 Standard Form Typ http://www.ipc.org/IPC-175x Distribute									s Materia	ials and Mfg Information				
Supplier Infor	mation															
Company name* Cor				Company unique ID			Unique ID Authority					Response Date*				
onsemi												2023-06-08				
Contact Name			Title - Conta	Title - Contact			Phone - Contact*					Email - Contact*				
Product-Env-Stev	wards	Product Enviro Compliance				NA					Product-Env-Stewards@onsemi.com					
Authorized Representative* Title				Title - Representative			Phone - Representative*				Email - Representative*					
Product-Env-Stev	wards	Product Enviro Compliance				NA					Product-Env-Stewards@onsemi.com					
Reque	ster Item Number	r Item Number Mfr Item Number Mfr Item Name AX5031-1-TW30 Radio Transmitte		em Number Mfr Item Name			Effective Date	e Version	ersion Manufacturing Site		Site	W	eight*	UOM	Unit Type	
				er		2023-06-08 PHG		HG		42	2.75	mg	Each			
Ianufacturin	g Proccess Informati	ion						<u> </u>								
Termin	nal Plating / Grid Array Material		Terminal Base Alloy		J-STD-020 M	ISL Rating Peak		Process Body Temperature Ma		e Max Time	at Peak	k Temperature Numb		ımber of Reflow Cycles		
Precious metal (e.g. Ag,Au, NiPdAu) (no Sn)			CU Alloy		1		260		C	30		second	3			
Comments																
vel 1 - maximum	n time at peak temperatur	e during so	ldering is 10-3	30 seconds												
or more informa	ation regarding material c	omposition	please refer to	page 3												

RoHS Material Composition Declaration			Declaration Type *	Detail	ed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).											
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on informationprovided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its suppliers have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies of Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply.											
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substar	nces per the definition above	Supplier A	cceptance *	Accepted						
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
		e "Accepted" on the Supplier Acceptance	drop-down. This will display the signature a	rea. Digitally sign t	the declaration (if required by the						

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	1.9	mg	Supplier	Silicon (Si)	7440-21-3		1.9	mg
Die Attach	0.58		Supplier	Epoxized Condensate Of Para- Hydrobenzaldehyde And Alkyl Phenol	129915-35-1		0.116	mg
			Supplier	Silver (Ag)	7440-22-4		0.464	mg
Lead Frame	16.1	mg	Supplier	Silver (Ag)	7440-22-4		0.322	mg
			Supplier	Iron (Fe)	7439-89-6		0.3542	mg
			Supplier	Copper (Cu)	7440-50-8		15.4238	mg
Mold Compound-Black	22.31		Supplier	Epoxy and Phenolic Resin	40216-08-8		1.7848	mg
			Supplier	Carbon Black (C)	1333-86-4		0.1115	mg
			Supplier	Aluminum Hydroxide (Al(OH)3)	21645-51-2		0.4462	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		19.2981	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		0.6693	mg
Plating	1.58	mg	Supplier	Tin (Sn)	7440-31-5		1.58	mg
Wire Bond - Au	0.28	mg	Supplier	Gold (Au)	7440-57-5		0.28	mg