

#### **Features**

- · High Current Capability and High Efficiency
- Halogen Free Available Upon Request By Adding Suffix "-HF"
- Epoxy Meets UL 94 V-0 Flammability Rating
- Moisture Sensitivity Level 1
- Lead Free Finish/RoHS Compliant(Note 1) ("P" Suffix Designates RoHS Compliant. See Ordering Information)

# **Maximum Ratings**

- Operating Junction Temperature Range: -55°C to +150°C
- Storage Temperature Range: -55°C to +150°C
- Typical Thermal Resistance: 2 °C/W Junction to Case


MCC Part Number	Device Marking	Maximum Recurrent Peak Reverse Voltage	Maximum RMS Voltage	Maximum DC Blocking Voltage
MBRB3030CT	MBRB3030CT	30V	21V	30V
MBRB3040CT	MBRB3040CT	40V	28V	40V
MBRB3045CT	MBRB3045CT	45V	31.5V	45V
MBRB3060CT	MBRB3060CT	60V	42V	60V

#### Electrical Characteristics @ 25°C Unless Otherwise Specified


Average Forward Current	I <sub>F(AV)</sub>	30A	T <sub>C</sub> =110°C
Peak Forward Surge Current	I <sub>FSM</sub>	250A	8.3ms,Half Sine
Maximum Instantaneous Forward Voltage MBRB3030CT-3045CT MBRB3060CT	$V_{F}$	0.60V 0.72V	I <sub>FM</sub> =15A; T <sub>J</sub> =25°C
Maximum DC Reverse Current at Rated DC Blocking Voltage	I <sub>R</sub>	0.1mA 10mA	T <sub>J</sub> =25°C T <sub>J</sub> =125°C
Typical Junction Capacitance	CJ	420pF	Measured at 1.0MHz, V <sub>R</sub> =4.0V

Note:1. High Temperature Solder Exemptions Applied, See EU Directive Annex Notes 7a.

## **Internal Structure**




# 30 Amp Schottky Barrier Rectifier 30 to 60 Volts



DIMENSIONS					
DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	NOTE
Α	0.331	0.370	8.40	9.40	
В	0.378	0.417	9.60	10.60	
С	0.165	0.189	4.20	4.80	
D	0.027	0.037	0.68	0.94	
E	0.045	0.055	1.14	1.40	
G	0.010		2.54		TYP.
Н	0.096	0.134	2.43	3.40	
J	0.011	0.025	0.28	0.64	
K	0.071	0.131	1.80	3.32	
S	0.575	0.625	14.60	15.87	
V	0.042	0.058	1.07	1.47	
W	0.000	0.010	0.00	0.25	

#### Suggested Solder Pad Layout





#### **Curve Characteristics**




Fig. 3 - Typical Instantaneous Forward Characteristics




Fig. 5 - Typical Reverse Leakage Characteristics




Fig. 2 - Maximum Non-Repetitive Peak Forward Surge Current 250 Peak Forward Surge Current (A) 200 150 100 50 8.3 ms Single Half Sine-Wave 0 100

Fig. 4 - Typical Instantaneous Forward Characteristics

Number of Cycles at 60 Hz





Fig. 6 - Typical Reverse Leakage Characteristics





### **Ordering Information**

Device	Packing	
Part Number-TP	Tape&Reel: 800pcs/Reel	
Part Number-BP	Tube: 5Kpcs/Ctn	

Note: Adding "-HF" Suffix For Halogen Free, eg. Part Number-TP-HF

#### \*\*\*IMPORTANT NOTICE\*\*\*

**Micro Commercial Components Corp.** reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp**. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp**, and all the companies whose products are represented on our website, harmless against all damages. **Micro Commercial Components Corp**, products are sold subject to the general terms and conditions of commercial sale, as published at

https://www.mccsemi.com/Home/TermsAndConditions.

#### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.