

## ATGBICS R0R41B-C network transceiver module Copper 10000 Mbit/s RJ-45

**Brand :** ATGBICS

**Product code:** R0R41B-C

**Product name :** R0R41B-C



R0R41B ATGBICS HPE Compatible Transceiver SFP+ 10G Base T RJ45 Connector 300m

[ATGBICS R0R41B-C network transceiver module Copper 10000 Mbit/s RJ-45:](#)

R0R41B 10GBase-T supports a distance of up to 300m over a copper connection via a RJ-45 connector. It is specifically designed for high speed communication links that require 10 Gigabit Ethernet over Cat 6a/7. Our product is built to the exact specification of HPE R0R41B= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.

ATGBICS R0R41B-C. SFP transceiver type: Copper, Maximum data transfer rate: 10000 Mbit/s, Interface type: RJ-45. Product colour: Silver, Housing material: Metal, Country of origin: United Kingdom. Input voltage: 3.3 V, Maximum voltage: 4 V, Power consumption (typical): 2.5 W. Width: 13.4 mm, Depth: 56.6 mm, Height: 8.5 mm. Number of products included: 1 pc(s), Package type: Box



Performance		Features	
SFP transceiver type *	Copper	Country of origin	United Kingdom
Maximum data transfer rate *	10000 Mbit/s	Brand compatibility	HP
Interface type *	RJ-45	<b>Power</b>	
Single-mode fiber (SMF) supported	✗	Input voltage	3.3 V
Multi-mode fiber (MMF) supported	✗	Maximum voltage	4 V
Fiber optic connector	SFP+	Power consumption (typical)	2.5 W
SFP transceiver standard	TX	<b>Operational conditions</b>	
Maximum transfer distance	300 m	Maximum operating temperature	70 °C
Ethernet LAN	✓	Operating temperature (T-T)	0 - 70 °C
Ethernet interface type	10 Gigabit Ethernet	Storage temperature (T-T)	-40 - 85 °C
Networking standards	IEEE 802.3az	Operating relative humidity (H-H)	5 - 95%
Copper ethernet cabling technology	10GBASE-TX	Storage relative humidity (H-H)	5 - 95%
Digital Diagnostics Monitoring (DDM)	✗	<b>Weight &amp; dimensions</b>	
<b>Features</b>		Width	13.4 mm
Product colour	Silver	Depth	56.6 mm
Housing material	Metal	Height	8.5 mm
Plug and Play	✓	Weight	24 g
Hot-Plug support	✓	<b>Packaging data</b>	
Hot-swap	✓	Number of products included	1 pc(s)
Easy to install	✓	Package type	Box
		<b>Technical details</b>	
		Sustainability certificates	RoHS



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.