

Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Protect It! 6-Outlet Surge Protector with 3 Rotatable Outlets – Direct Plug-In, 1200 Joules, 2 USB Ports

MODEL NUMBER: SWIVEL6USB











Swivel surge protector with USB safeguards your home/office electronics against dangerous surges, spikes and line noise.

Features

Swivel Surge Protector with USB Safeguards Your Sensitive Electronics Ideal for your home or office workstation, this Protect Itl® 6-outlet swivel surge protector features a surge protection rating of 1200 joules to defend your sensitive electronic components against even strong power surges and spikes. Because residential power outlets have three wires—hot line (H), neutral (N) and ground (G)—the SWIVEL6USB protects all three, covering the two protection modes: full normal mode (H-N) and common mode (N-G/H-G).

6 Outlets Accept a Wide Range of Electronic DevicesThe direct plug-in design converts two standard wall outlets into six. Plug your PC, printer, scanner, router, modem, television, stereo receiver and other home/office electronics into six NEMA 5-15R AC outlets to protect them against dangerous surges, spikes and line noise.

2 USB Ports Share 3.1 Amps of Charging PowerDual USB-A ports are available for charging your smartphone, tablets and other USB mobile devices, which are also protected from the damaging effects of surges, spikes and line interference.

Rotating Outlets Help Accommodate Bulky TransformersThree of the six outlets rotate 90 degrees to allow great flexibility in placing connected devices or accepting bulky transformers without blocking adjacent outlets.

Premium Protection from EMI/RFI Line Noise Helps Your Equipment Perform Better Various electromagnetic and radio sources found in virtually every home and business can cause disruptive interference on the AC line. Known as EMI (electromagnetic interference) and RFI (radio frequency interference), this line noise is a common cause of performance problems. This swivel surge protector with USB filters out disruptive line noise that can disturb your electronics and inflict hardware damage or data loss. This EMI/RFI filtering also helps your connected components perform better with longer lifespans.

Includes the Latest Safety FeaturesAn integrated 15A circuit breaker protects all outlets and automatically cuts power to outlets if protection circuit is incapacitated, preventing equipment damage and

Highlights

- Rotating outlets accommodate bulky transformers without blocking other outlets
- 1200 joules protect your valuable electronics against dangerous surges/spikes/line noise
- Direct plug-in design (no power cord) for easy transport in briefcase or luggage
- 2 USB ports share 3.1A for fast charging of phone, laptop and other mobile devices

Applications

- Protecting computers, modems, home theater equipment and other valuable electronics against AC power surges and spikes
- Filtering potentially damaging line noise to improve connected equipment's performance and lifespans
- Safeguarding valuable data against damage stemming from unexpected interruptions in power
- Charging a smartphone, tablet or other USB devices via the dual USB ports

Package Includes

- SWIVEL6USB Protect It! 6-Outlet Surge Protector with 3 Rotatable Outlets – Direct Plug-In, 1200 Joules, 2 USB Ports
- Owner's manual



indicating replacement is required. Diagnostic LEDs confirm your wall outlet is properly grounded and your connected equipment is protected. The 6-outlet swivel surge protector conforms to current UL 1449 3rd Edition and cUL (Canada) safety standards. Its high-impact black plastic housing is designed to endure in demanding environments.

Lifetime Warranty, \$20K Ultimate Lifetime Insurance and Environmentally Responsible DesignThe SWIVEL6USB comes with a lifetime warranty and \$20,000 of Ultimate Lifetime Insurance for any connected components damaged by a power surge (U.S., Canada and Puerto Rico only). It's manufactured in compliance with strict RoHS specifications, reflecting Tripp Lite's commitment to environmental responsibility.

Specifications

| OVERVIEW | | |
|------------------------------------|------------------------------|--|
| UPC Code | 037332210944 | |
| Product Type | Surge Protector | |
| Charging Form Factor | Strip | |
| Device Compatibility | Phone; Tablet; Amazon Kindle | |
| INPUT | | |
| Nominal Input Voltage(s) Supported | 120V AC | |
| Recommended Electrical Service | 120V (110-125V) | |
| Input Cord Length Details | Direct plug-in | |
| Voltage Compatibility (VAC) | 120 | |
| Maximum Surge Amps | 60000 | |
| Input Plug Type | NEMA 5-15P | |
| Input Cord Length (ft.) | 0 | |
| Right-Angle Plug | No | |
| Input Cord Length (m) | 0.00 | |
| Integrated Cord Clip | No | |
| ОИТРИТ | | |
| Frequency Compatibility | 60 Hz | |
| Output (Watts) | 1800 | |
| Output Receptacles | (6) 5-15R | |
| Circuit Breaker (amps) | 15 | |
| Transformer Accommodation | (2) Yes | |
| Outlet Orientation | Rotatable | |
| Right-Angle Outlets | No | |



| USER INTERFACE, ALERTS & CONTROLS | | |
|--|--|--|
| Diagnostic LED(s) | Yes | |
| Diagnostic LED Details | Built-in LEDs confirm suppressor "protected" (green) and "grounded" (red) status | |
| SURGE / NOISE SUPPRESSION | | |
| AC Suppression Joule Rating | 1200 | |
| AC Suppression Response Time | <1 ns | |
| Protection Modes | Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression | |
| UL1449 Let Through Rating | 800, 800, 800 | |
| EMI / RFI Filtering | 150 kHz to 100 mHz | |
| Automatic Shut-Off | No | |
| CHARGING | | |
| Number of Charging Ports | 2 | |
| Charging Method | USB | |
| Charging Port Type | USB A (FEMALE) | |
| Charging Ports / Amps | (2) 3.1A | |
| DATALINE SURGE SUPPRESSION | | |
| Telephone/DSL Protection | No | |
| Cable (Coax) Protection | No | |
| Network (Ethernet) Protection | No | |
| PHYSICAL | | |
| Antimicrobial | No | |
| Housing Color | Black | |
| Integrated Keyhole Mounting Slots | No | |
| Material of Construction | Plastic | |
| Outlets Measurement (Center to Center) | 29mm | |
| Receptacle Color | Black | |
| Shipping Dimensions (hwd / cm) | 19.20 x 11.40 x 5.79 | |
| Shipping Dimensions (hwd / in.) | 7.56 x 4.49 x 2.28 | |
| Shipping Weight (kg) | 0.33 | |
| Shipping Weight (lbs.) | 0.72 | |
| Unit Dimensions (hwd / in.) | 5.47 x 3.94 x 2.28 | |
| Unit Weight (kg) | 0.00 | |



Tripp Lite1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

| Unit Weight (lbs.) | 0.00 | |
|--|---|--|
| | | |
| FEATURES & SPECIFICATIONS | | |
| Rotatable Outlets | Yes | |
| | | |
| STANDARDS & COMPLIANCE | | |
| Canada | Approved for Canada by ETL | |
| Approvals | RoHS | |
| UL1449 3rd Edition (AC Suppression) | Tested to UL1449 3RD EDITION Requirements by ETL | |
| | | |
| WARRANTY | | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty | |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$20,000 Ultimate Lifetime Insurance | |

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies