


## R76MR410040H4H

Aliases (76MR410040H4H)

R76H, Film, Double Metallized Polypropylene, Automotive Grade, 1  $\mu$ F, 2.5%, 400 VDC, 105°C, Lead Spacing = 27.5mm



Click [here](#) for the 3D model.

### Dimensions

L	32mm +0.3/-0.7mm
H	22mm +0.1/-0.7mm
T	13mm +0.2/-0.7mm
S	27.5mm +/-0.4mm
LL	30mm +5mm
F	0.8mm +/-0.05mm

### Packaging Specifications

Packaging	Tray
Packaging Quantity	288

### General Information

Series	R76H
Dielectric	Double Metallized Polypropylene
Style	Radial
Features	Automotive Grade, Pulse
RoHS	Yes
Lead	Wire Leads
Qualifications	AEC-Q200
AEC-Q200	Yes
THB Performance	Yes
Component Weight	10.2 g

### Specifications

Capacitance	1 $\mu$ F
Capacitance Tolerance	2.5%
Voltage AC	250 VAC
Voltage DC	400 VDC
Temperature Range	-55/+125°C
Rated Temperature	105°C
Dissipation Factor	0.03% 1kHz, 0.06% 10kHz
Insulation Resistance	30 GOhms
Max dV/dt	300 V/us
Resistance	5.57 mOhms (100kHz)
Ripple Current	9.74 Amps (100kHz 100C), 300 Amps (Peak)
Inductance	18 nH