



Power contactor, AC-3 12 A, 5.5 kW / 400 V 1 NO, 600 V AC, 60 Hz 3-pole, Size S00 screw terminal

|   |                                       |
|---|---------------------------------------|
| <b>product brand name</b>   | SIRIUS                                |
| <b>product designation</b>  | Power contactor                       |
| <b>product type designation</b>   | 3RT2                                  |
| <b>General technical data</b>   |                                       |
| <b>size of contactor</b>  | S00                                   |
| <b>product extension</b>  |                                       |
| <ul style="list-style-type: none"> <li>function module for communication</li> <li>auxiliary switch</li> </ul>   | No<br>Yes                             |
| <b>power loss [W] for rated value of the current</b>  |                                       |
| <ul style="list-style-type: none"> <li>at AC in hot operating state</li> <li>at AC in hot operating state per pole</li> <li>without load current share typical</li> </ul>   | 1.5 W<br>0.5 W<br>6.5 W               |
| <b>insulation voltage</b>   |                                       |
| <ul style="list-style-type: none"> <li>of main circuit with degree of pollution 3 rated value</li> <li>of auxiliary circuit with degree of pollution 3 rated value</li> </ul>   | 690 V<br>690 V                        |
| <b>surge voltage resistance</b>   |                                       |
| <ul style="list-style-type: none"> <li>of main circuit rated value</li> <li>of auxiliary circuit rated value</li> </ul>   | 6 kV<br>6 kV                          |
| maximum permissible voltage for safe isolation between coil and main contacts according to EN 60947-1   | 400 V                                 |
| <b>shock resistance at rectangular impulse</b>  |                                       |
| <ul style="list-style-type: none"> <li>at AC</li> </ul>   | 7,3g / 5 ms, 4,7g / 10 ms             |
| <b>shock resistance with sine pulse</b>   |                                       |
| <ul style="list-style-type: none"> <li>at AC</li> </ul>   | 11,4g / 5 ms, 7,3g / 10 ms            |
| <b>mechanical service life (switching cycles)</b>   |                                       |
| <ul style="list-style-type: none"> <li>of contactor typical</li> <li>of the contactor with added electronically optimized auxiliary switch block typical</li> <li>of the contactor with added auxiliary switch block typical</li> </ul> | 30 000 000<br>5 000 000<br>10 000 000 |
| <b>reference code according to IEC 81346-2</b>  | Q                                     |
| <b>Substance Prohibitance (Date)</b>  | 10/01/2009                            |
| <b>Ambient conditions</b>   |                                       |
| installation altitude at height above sea level maximum   | 2 000 m                               |
| <b>ambient temperature</b>  |                                       |
| <ul style="list-style-type: none"> <li>during operation</li> <li>during storage</li> </ul>  | -25 ... +60 °C<br>-55 ... +80 °C      |
| <b>relative humidity minimum</b>  | 10 %                                  |
| <b>relative humidity at 55 °C according to IEC 60068-2-30 maximum</b>   | 95 %                                  |

## Main circuit

|  |                   |
|--|-------------------|
| <b>number of poles for main current circuit</b>                        | 3                 |
| <b>number of NO contacts for main contacts</b>                         | 3                 |
| <b>operating voltage</b>   |                   |
| • at AC-3 rated value maximum  | 690 V             |
| • at AC-3e rated value maximum   | 690 V             |
| <b>operational current</b>   |                   |
| • at AC-1 at 400 V at ambient temperature 40 °C rated value            | 22 A              |
| • at AC-1  |                   |
| — up to 690 V at ambient temperature 40 °C rated value                 | 22 A              |
| — up to 690 V at ambient temperature 60 °C rated value                 | 20 A              |
| • at AC-3  |                   |
| — at 400 V rated value   | 12 A              |
| — at 500 V rated value   | 9.2 A             |
| — at 690 V rated value   | 6.7 A             |
| • at AC-3e   |                   |
| — at 400 V rated value   | 12 A              |
| — at 500 V rated value   | 9.2 A             |
| — at 690 V rated value   | 6.7 A             |
| • at AC-4 at 400 V rated value   | 8.5 A             |
| • at AC-5a up to 690 V rated value                                     | 19.4 A            |
| • at AC-5b up to 400 V rated value                                     | 9.9 A             |
| • at AC-6a   |                   |
| — up to 230 V for current peak value n=20 rated value                  | 7.2 A             |
| — up to 400 V for current peak value n=20 rated value                  | 7.2 A             |
| — up to 500 V for current peak value n=20 rated value                  | 7.2 A             |
| — up to 690 V for current peak value n=20 rated value                  | 6.7 A             |
| • at AC-6a   |                   |
| — up to 230 V for current peak value n=30 rated value                  | 4.8 A             |
| — up to 400 V for current peak value n=30 rated value                  | 4.8 A             |
| — up to 500 V for current peak value n=30 rated value                  | 4.8 A             |
| — up to 690 V for current peak value n=30 rated value                  | 4.8 A             |
| minimum cross-section in main circuit at maximum AC-1 rated value      | 4 mm <sup>2</sup> |
| <b>operational current for approx. 200000 operating cycles at AC-4</b> |                   |
| • at 400 V rated value   | 4.1 A             |
| • at 690 V rated value   | 3.3 A             |
| <b>operational current</b>   |                   |
| • <b>at 1 current path at DC-1</b>                                     |                   |
| — at 24 V rated value  | 20 A              |
| — at 110 V rated value   | 2.1 A             |
| — at 220 V rated value   | 0.8 A             |
| — at 440 V rated value   | 0.6 A             |
| — at 600 V rated value   | 0.6 A             |
| • <b>with 2 current paths in series at DC-1</b>                        |                   |
| — at 24 V rated value  | 20 A              |
| — at 110 V rated value   | 12 A              |
| — at 220 V rated value   | 1.6 A             |
| — at 440 V rated value   | 0.8 A             |
| — at 600 V rated value   | 0.7 A             |
| • <b>with 3 current paths in series at DC-1</b>                        |                   |

|   |   |
|---|---|
| — at 24 V rated value   | 20 A  |
| — at 110 V rated value  | 20 A  |
| — at 220 V rated value  | 20 A  |
| — at 440 V rated value  | 1.3 A   |
| — at 600 V rated value  | 1 A   |
| ● <b>at 1 current path at DC-3 at DC-5</b>                              |   |
| — at 24 V rated value   | 20 A  |
| — at 110 V rated value  | 0.1 A   |
| ● <b>with 2 current paths in series at DC-3 at DC-5</b>                 |   |
| — at 24 V rated value   | 20 A  |
| — at 110 V rated value  | 0.35 A  |
| ● <b>with 3 current paths in series at DC-3 at DC-5</b>                 |   |
| — at 24 V rated value   | 20 A  |
| — at 110 V rated value  | 20 A  |
| — at 220 V rated value  | 1.5 A   |
| — at 440 V rated value  | 0.2 A   |
| — at 600 V rated value  | 0.2 A   |
| <b>operating power</b>  |   |
| ● at AC-2 at 400 V rated value  | 5.5 kW  |
| ● at AC-3   |   |
| — at 230 V rated value  | 3 kW  |
| — at 400 V rated value  | 5.5 kW  |
| — at 500 V rated value  | 5.5 kW  |
| — at 690 V rated value  | 5.5 kW  |
| ● at AC-3e  |   |
| — at 230 V rated value  | 3 kW  |
| — at 400 V rated value  | 5.5 kW  |
| — at 500 V rated value  | 5.5 kW  |
| — at 690 V rated value  | 5.5 kW  |
| <b>operating power for approx. 200000 operating cycles at AC-4</b>      |   |
| ● at 400 V rated value  | 2 kW  |
| ● at 690 V rated value  | 2.5 kW  |
| <b>operating apparent power at AC-6a</b>                                |   |
| ● up to 230 V for current peak value n=20 rated value                   | 2.8 kVA   |
| ● up to 400 V for current peak value n=20 rated value                   | 4.9 kVA   |
| ● up to 500 V for current peak value n=20 rated value                   | 6.2 kVA   |
| ● up to 690 V for current peak value n=20 rated value                   | 8 kVA   |
| <b>operating apparent power at AC-6a</b>                                |   |
| ● up to 230 V for current peak value n=30 rated value                   | 1.9 kVA   |
| ● up to 400 V for current peak value n=30 rated value                   | 3.3 kVA   |
| ● up to 500 V for current peak value n=30 rated value                   | 4.1 kVA   |
| ● up to 690 V for current peak value n=30 rated value                   | 5.7 kVA   |
| <b>short-time withstand current in cold operating state up to 40 °C</b> |   |
| ● limited to 1 s switching at zero current maximum                      | 200 A; Use minimum cross-section acc. to AC-1 rated value |
| ● limited to 5 s switching at zero current maximum                      | 123 A; Use minimum cross-section acc. to AC-1 rated value |
| ● limited to 10 s switching at zero current maximum                     | 96 A; Use minimum cross-section acc. to AC-1 rated value  |
| ● limited to 30 s switching at zero current maximum                     | 74 A; Use minimum cross-section acc. to AC-1 rated value  |
| ● limited to 60 s switching at zero current maximum                     | 61 A; Use minimum cross-section acc. to AC-1 rated value  |
| <b>no-load switching frequency</b>                                      |   |
| ● at AC   | 10 000 1/h  |
| <b>operating frequency</b>  |   |
| ● at AC-1 maximum   | 1 000 1/h   |
| ● at AC-2 maximum   | 750 1/h   |
| ● at AC-3 maximum   | 750 1/h   |
| ● at AC-3e maximum  | 750 1/h   |
| ● at AC-4 maximum   | 250 1/h   |
| <b>Control circuit/ Control</b>   |   |
| <b>type of voltage of the control supply voltage</b>                    | AC  |

|   |  |
|---|--|
| <b>control supply voltage at AC</b><br>• at 60 Hz rated value   | 600 V  |
| <b>operating range factor control supply voltage rated value of magnet coil at AC</b><br>• at 60 Hz   | 0.85 ... 1.1   |
| <b>apparent pick-up power of magnet coil at AC</b><br>• at 60 Hz  | 43 VA  |
| <b>inductive power factor with closing power of the coil</b><br>• at 60 Hz  | 0.8  |
| <b>apparent holding power of magnet coil at AC</b><br>• at 60 Hz  | 6.5 VA   |
| <b>inductive power factor with the holding power of the coil</b><br>• at 60 Hz  | 0.25   |
| <b>closing delay</b><br>• at AC   | 9 ... 35 ms  |
| <b>opening delay</b><br>• at AC   | 7 ... 13 ms  |
| <b>arcing time</b>  | 10 ... 15 ms   |
| <b>control version of the switch operating mechanism</b>  | Standard A1 - A2                                     |
| <b>Auxiliary circuit</b>  |  |
| number of NO contacts for auxiliary contacts<br>instantaneous contact   | 1  |
| operational current at AC-12 maximum  | 10 A   |
| <b>operational current at AC-15</b><br>• at 230 V rated value<br>• at 400 V rated value<br>• at 500 V rated value<br>• at 690 V rated value   | 10 A<br>3 A<br>2 A<br>1 A                            |
| <b>operational current at DC-12</b><br>• at 24 V rated value<br>• at 48 V rated value<br>• at 60 V rated value<br>• at 110 V rated value<br>• at 125 V rated value<br>• at 220 V rated value<br>• at 600 V rated value  | 10 A<br>6 A<br>6 A<br>3 A<br>2 A<br>1 A<br>0.15 A    |
| <b>operational current at DC-13</b><br>• at 24 V rated value<br>• at 48 V rated value<br>• at 60 V rated value<br>• at 110 V rated value<br>• at 125 V rated value<br>• at 220 V rated value<br>• at 600 V rated value  | 10 A<br>2 A<br>2 A<br>1 A<br>0.9 A<br>0.3 A<br>0.1 A |
| <b>contact reliability of auxiliary contacts</b>  | 1 faulty switching per 100 million (17 V, 1 mA)      |
| <b>UL/CSA ratings</b>   |  |
| <b>full-load current (FLA) for 3-phase AC motor</b><br>• at 480 V rated value<br>• at 600 V rated value   | 11 A<br>11 A   |
| <b>yielded mechanical performance [hp]</b><br>• for single-phase AC motor<br>— at 110/120 V rated value<br>— at 230 V rated value<br>• for 3-phase AC motor<br>— at 200/208 V rated value<br>— at 220/230 V rated value<br>— at 460/480 V rated value<br>— at 575/600 V rated value | 0.5 hp<br>2 hp<br>3 hp<br>3 hp<br>7.5 hp<br>10 hp    |
| <b>contact rating of auxiliary contacts according to UL</b>   | A600 / Q600  |

| Short-circuit protection   |  |
|--|--|
| <b>design of the fuse link</b> <ul style="list-style-type: none"> <li>● for short-circuit protection of the main circuit <ul style="list-style-type: none"> <li>— with type of coordination 1 required</li> <li>— with type of assignment 2 required</li> </ul> </li> <li>● for short-circuit protection of the auxiliary switch required</li> </ul>   | gG: 50A (690V,100kA), aM: 20A (690V,100kA), BS88: 35A (415V,80kA)<br>gG: 20A (690V,100kA), aM: 16A (690V, 100kA), BS88: 20A (415V, 80kA)<br>gG: 10 A (500 V, 1 kA) |
| Installation/ mounting/ dimensions   |  |
| <b>mounting position</b>   | +/-180° rotation possible on vertical mounting surface; can be tilted forward and backward by +/- 22.5° on vertical mounting surface                               |
| <b>fastening method</b> <ul style="list-style-type: none"> <li>● side-by-side mounting</li> </ul>  | screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 60715<br>Yes  |
| <b>height</b>  | 58 mm  |
| <b>width</b>   | 45 mm  |
| <b>depth</b>   | 73 mm  |
| <b>required spacing</b> <ul style="list-style-type: none"> <li>● with side-by-side mounting <ul style="list-style-type: none"> <li>— forwards 10 mm</li> <li>— upwards 10 mm</li> <li>— downwards 10 mm</li> <li>— at the side 0 mm</li> </ul> </li> <li>● for grounded parts <ul style="list-style-type: none"> <li>— forwards 10 mm</li> <li>— upwards 10 mm</li> <li>— at the side 6 mm</li> <li>— downwards 10 mm</li> </ul> </li> <li>● for live parts <ul style="list-style-type: none"> <li>— forwards 10 mm</li> <li>— upwards 10 mm</li> <li>— downwards 10 mm</li> <li>— at the side 6 mm</li> </ul> </li> </ul> |  |
| Connections/ Terminals   |  |
| <b>type of electrical connection</b> <ul style="list-style-type: none"> <li>● for main current circuit</li> <li>● for auxiliary and control circuit</li> <li>● at contactor for auxiliary contacts</li> <li>● of magnet coil</li> </ul>  | screw-type terminals<br>screw-type terminals<br>Screw-type terminals<br>Screw-type terminals   |
| <b>type of connectable conductor cross-sections</b> <ul style="list-style-type: none"> <li>● for main contacts <ul style="list-style-type: none"> <li>— solid 2x (0.5 ... 1.5 mm<sup>2</sup>), 2x (0.75 ... 2.5 mm<sup>2</sup>), 2x 4 mm<sup>2</sup></li> <li>— solid or stranded 2x (0,5 ... 1,5 mm<sup>2</sup>), 2x (0,75 ... 2,5 mm<sup>2</sup>), 2x 4 mm<sup>2</sup></li> <li>— finely stranded with core end processing 2x (0.5 ... 1.5 mm<sup>2</sup>), 2x (0.75 ... 2.5 mm<sup>2</sup>)</li> </ul> </li> <li>● at AWG cables for main contacts 2x (20 ... 16), 2x (18 ... 14), 2x 12</li> </ul>                     |  |
| <b>connectable conductor cross-section for main contacts</b> <ul style="list-style-type: none"> <li>● solid 0.5 ... 4 mm<sup>2</sup></li> <li>● stranded 0.5 ... 4 mm<sup>2</sup></li> <li>● finely stranded with core end processing 0.5 ... 2.5 mm<sup>2</sup></li> </ul>  |  |
| <b>connectable conductor cross-section for auxiliary contacts</b> <ul style="list-style-type: none"> <li>● solid or stranded 0.5 ... 4 mm<sup>2</sup></li> <li>● finely stranded with core end processing 0.5 ... 2.5 mm<sup>2</sup></li> </ul>  |  |
| <b>type of connectable conductor cross-sections</b> <ul style="list-style-type: none"> <li>● for auxiliary contacts <ul style="list-style-type: none"> <li>— solid or stranded 2x (0.5 ... 1.5 mm<sup>2</sup>), 2x (0.75 ... 2.5 mm<sup>2</sup>), 2x 4 mm<sup>2</sup></li> <li>— finely stranded with core end processing 2x (0.5 ... 1.5 mm<sup>2</sup>), 2x (0.75 ... 2.5 mm<sup>2</sup>)</li> </ul> </li> <li>● at AWG cables for auxiliary contacts 2x (20 ... 16), 2x (18 ... 14), 2x 12</li> </ul>   |  |
| <b>AWG number as coded connectable conductor cross section</b>   |  |

- for main contacts 20 ... 12
- for auxiliary contacts 20 ... 12

### Safety related data

|   |  |
|---|--|
| <b>product function</b>   |  |
| <ul style="list-style-type: none"> <li>• mirror contact according to IEC 60947-4-1</li> </ul>   | Yes; with 3RH29                                  |
| B10 value with high demand rate according to SN 31920   | 1 000 000  |
| <b>proportion of dangerous failures</b>   |  |
| <ul style="list-style-type: none"> <li>• with low demand rate according to SN 31920</li> </ul>  | 40 %   |
| <ul style="list-style-type: none"> <li>• with high demand rate according to SN 31920</li> </ul> | 73 %   |
| failure rate [FIT] with low demand rate according to SN 31920                                   | 100 FIT  |
| T1 value for proof test interval or service life according to IEC 61508                         | 20 y   |
| <b>protection class IP on the front according to IEC 60529</b>                                  | IP20   |
| <b>touch protection on the front according to IEC 60529</b>                                     | finger-safe, for vertical contact from the front |
| <b>suitability for use</b>  |  |
| <ul style="list-style-type: none"> <li>• safety-related switching OFF</li> </ul>                | Yes  |

### Certificates/ approvals

#### General Product Approval



[Confirmation](#)



[KC](#)



|     |                                       |                           |                   |
|-----|---------------------------------------|---------------------------|-------------------|
| EMC | Functional Safety/Safety of Machinery | Declaration of Conformity | Test Certificates |
|-----|---------------------------------------|---------------------------|-------------------|



[Type Examination Certificate](#)



EG-Konf.



[Type Test Certificates/Test Report](#)

[Special Test Certificate](#)

### Marine / Shipping



|                   |       |
|-------------------|-------|
| Marine / Shipping | other |
|-------------------|-------|



[Confirmation](#)



### Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=3RT2017-1AT61>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mfb=3RT2017-1AT61>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RT2017-1AT61>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RT2017-1AT61&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT2017-1AT61&lang=en)

**Characteristic: Tripping characteristics,  $I^2t$ , Let-through current**

<https://support.industry.siemens.com/cs/ww/en/ps/3RT2017-1AT61/char>

**Further characteristics (e.g. electrical endurance, switching frequency)**

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RT2017-1AT61&objecttype=14&gridview=view1>

last modified:

6/2/2022 