		Π	m		0			
EXPLICIENT CARACTERISTICS         Shell Materia is composite         Shell Materia is control using codes         Delivered with Souriau contacts and Accessones         Thermoproture Range : 65°C to 175°C         Shell Series:       80         Basic SERIES:       13								
CHARCTENSTCS         -Standard: Based on MIL-DT-38999 Series III         -Standard: Based on MIL-DT-38999 Series III         -Standard: Based on MIL-DT-38999 Series III         -Shell Matrief ia: : Composite         -Shell Pating: : : Collect data Catamium         -Shell Pating: : : : Sudd wer copper Alloy         -Seals & Grommet: : : Slicon Flastomer         -Contact Haring: : : : : : : : : : : : : : : : : : :	S	~~~~~~			LAYOUT SI	HOWN AS EXAMPLE		
Shell Material       ::::::::::::::::::::::::::::::::::::		Keying Shown a	Connector dimension					
- Ourability       :: 500 Mating cycles         - Durability       :: 500 Mating cycles         - Delivered with Souriau contacts and Accessories         - Temperature Range       :: 65°C to +175°C         - Sait Spray       : 20.9 g ± 10%         Mass       : 20.9 g ± 10%         BASIC SERIES:       8D         SHELL TYPE       : Plug with RFI Shielding         CONTACT TYPE       : Standard Crimp Contact         SHELL SIZE : 13       . ORIENTATION : N         PLATING       : J         PLATING       : J         OWWW.SOURIAU.COM       This document is the property of communicated without permission         CONTACT TYPE       : SOURIAU         WWW.SOURIAU.COM       It must not be reproduced or communicated without permission	-Shell Material: Composite-Shell Plating: Olive drab Cadmium-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastomer		ØS 29.4 Max Z' 31.5 Max		due to a use of the I the Specifications issued	Products which does not cor by either of the Parties or b commendation, technical no Country Jurisdi	nply with y a third party otice.) iction & Control List	
-Salt Spray : 2000 hours -Mass : 20.9 g ± 10% A 17-10-2016 First Release ISS DATE Latest modification - by MOD N° Designed By: Date: CUSTOMER DRAWING Designed By: Date: CUSTOMER DRAWING Designed By: Date: COMPOSITE Plug 8D series SCALE General linear Tolerances: 859 ± 859 SCALE NPRDS / PROJECT Tolerances: ± 859 ± 859 This document is the property of SURIAU it must not be reproduced or communicated without permission FORMAT SOURIAU DRG N° SHEET	-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories				PN: 8			
BASIC SERIES:       8D       5       -       13       J       04       S       N         SHELL TYPE : Plug with RFI Shielding       General linear       SCALE       Ma       General linear       NPRDS / PROJECT         CONTACT TYPE : Standard Crimp Contact       ORIENTATION : N       NA       General linear       NPRDS / PROJECT       859         SHELL SIZE : 13       ONTACT TYPE : SOCKET(500 Matings)       ONTACT TYPE : SOCKET(500 Matings)       SOURIAU       This document is the propoduced or communicated without permission         PLATING :: J = Olive drab Cadmium       CONTACT LAYOUT : 13-04       FORMAT       SOURIAU DRG N°       SHEET	-Salt Spray : 2000 hours			ISS DATE	Latest modification - by			)D N°
BASIC SERIES.       ab       3       -       15       J       04       3       N       N       Tolerances:       859         SHELL TYPE : Plug with RFI Shielding       CONTACT TYPE : Standard Crimp Contact       ORIENTATION : N       NA       WWW.SOURIAU.COM       This document is the property of SOURIAU         SHELL SIZE : 13       CONTACT TYPE : SOCKET(500 Matings)       CONTACT LAYOUT : 13-04       FORMAT       SOURIAU DRG N°       SHEET				TITLE		Composite Plug 8	D series	
CONTACT TYPE : Standard Crimp Contact       ORIENTATION : N         SHELL SIZE : 13       CONTACT TYPE : SOCKET(500 Matings)         PLATING : J = Olive drab Cadmium       CONTACT LAYOUT : 13-04             FORMAT       SOURIAU             SOURIAU       SOURIAU             SOURIAU       SOURIAU             SOURIAU       SOURIAU		04 S N				olerances:	859	
				SOURIAL	J WWW.SOU	JRIAU.COM	SOURIAU it must not be reproduced or	
8D513J04SN-C	PLATING : J = Olive drab Cadmium		CONTACT LAYOUT	FORMAT A3		URIAU DRG N° D513J04SN-C		HEET 1/2

ſ	<b></b>	ര	וד	m	D	0
		Contact Layout				
4	×	$ \begin{array}{c}                                     $				
	Conta position A B C D Shell Arrangement N size no. c 13 -4	+.000 (0.00) +.150 (3.81) +.146 (3.71) +.035 (0.89) +.000 (0.00)083 (2.11) 146 (3.71) +.035 (0.89)				
ω						
	1					
	F					SOURIAU shall not be liable for an due to a use of the Products wi the Specifications issued by either o (professional recommenda
N						Count FR
						PN: 8D513
						016 First Release
_					ISS DATE Designed By:	Latest modification - by Date:
					TITLE	Compo
<b>→</b>					SCALE	General linear Tolerances: ±
					SOURIA	U WWW.SOURIAU.C
					FORMAT A3	SOURIAU 8D513J
L	Н	G	F	E	D	C

