

**LINEAR TECHNOLOGY MATERIALS DECLARATION**

1t3013befe#pbf

(Engineering Calculation)

TSSOP Exp. Pad

(printed on: 2020-07-11 20:23:53)

**TOTAL MASS (g) : 0.067339**

COMPONENT MATERIAL	VENDOR/ INDUSTRY NAMES	CONSTITUENT NAME	CAS NUMBER	CONSTITUENT MASS (g)	CONSTITUENT (PPM) OF MATERIAL	CONSTITUENT (PPM) OF TOTAL PKG.		
Active Device	Linear Technology	Silicon (Si)	7440-21-3	0.003515	1000000	52198.6445312		
Die Coat	Dow Corning	Silicone	69430-27-9	0.000000	0	0		
Lead Frame	Cu	Copper (Cu)	7440-50-8	0.025576	975000	379810.09375		
		Iron (Fe)	7439-89-6	0.000630	24000	9355.66015625		
		Phosphorus (P)	7723-14-0	0.000008	300	118.802032471		
		Zinc (Zn)	7440-66-6	0.000018	700	267.304595947		
		Nickel (Ni)	7440-02-0	0.000000	0	0		
		Silicon (Si)	7440-21-3	0.000000	0	0		
		Magnesium (Mg)	7439-95-4	0.000000	0	0		
		Tin (Sn)	7440-31-5	0.000000	0	0		
<b>Lead Frame Total:</b>				<b>0.026232</b>	<b>1000000</b>	<b>389551.875</b>		
Plating	PMI	Exter. Plating Pb	7439-92-1	0.000000	0	0		
		Exter. Plating Sn	7440-31-5	0.002364	1000000	35104.6640625		
		<b>External Plating Total:</b>				<b>0.002364</b>	<b>1000000</b>	<b>35104.6640625</b>
		Inter. Plating Ni	7440-02-0	0.000000	0	0		
		Inter. Plating Ag	7440-22-4	0.001030	1000000	15295.7626953		
<b>Internal Plating Total:</b>				<b>0.001030</b>	<b>1000000</b>	<b>15295.7626953</b>		
Die Attach	ELECTRICALLY CONDUCTIVE ADHESIVE	Silver (Ag)	7440-22-4	0.001034	750000	15355.1621094		
		Tin (Sn)	7440-31-5	0.000000	0	0		
		Lead (Pb)	7439-92-1	0.000000	0	0		
		Silica (SiO2)	60676-86-0	0.000000	0	0		
		Indium (In)	7440-74-6	0.000000	0	0		
		Metal Oxide		0.000000	0	0		
		Antimony (Sb)	7440-36-0	0.000000	0	0		
		Resin (EP)		0.000345	250000	5123.33789062		
<b>Die Attach Total:</b>				<b>0.001379</b>	<b>1000000</b>	<b>20478.5019531</b>		
Encapsulation	MULTI-AROMATIC RESIN Br/Sb FREE	Resin (EP)		0.003348	103000	49718.6523438		
		Bromine (Br)	40039-93-8	0.000000	0	0		
		Silica (SiO2)	60676-86-0	0.029088	895000	431964.1875		
		Antimony Trioxide (Sb2O3)	1309-64-4	0.000000	0	0		
		Metal Hydroxide		0.000000	0	0		
		Carbon Black (C)	1333-86-4	0.000065	2000	965.266540527		
		<b>Encapsulation Total:</b>				<b>0.032501</b>	<b>1000000</b>	<b>482648.125</b>
Bond Wire Estimated	AFW/TANAKA/ Kn	Gold (Au)	7440-57-5	0.000318	1000000	4722.38085938		
					<b>TOTAL MASS (g) :</b>	<b>0.067339</b>		