



MAX9589 Evaluation Kit

Evaluates: MAX9589

General Description

The MAX9589 evaluation kit (EV kit) is an assembled and tested PCB that demonstrates the MAX9589 quad-channel, standard-definition video filter amplifier with AC-coupled inputs. The EV kit operates from 2.7V to 3.6V with a 2V/V fixed gain.

Component List

DESIGNATION	QTY	DESCRIPTION
C1	1	10 μ F \pm 10%, 6.3V X5R ceramic capacitor (0805) Murata GRM21BR60J106K TDK C2012X5R0J106K
C2–C6	5	0.1 μ F \pm 10%, 16V X7R ceramic capacitors (0603) Taiyo Yuden EMK107BJ104KA TDK C1608X7R1C104KT or equivalent
C7–C10	0	Not installed, aluminum electrolytic capacitors (6.3mm x 6.0mm)
IN_A, IN_B, IN_C, IN_D, OUT_A, OUT_B, OUT_C, OUT_D	8	75 Ω BNC PCB-mount jack connectors
R1–R8	8	75 Ω \pm 1% resistors (0603)
R9–R12	4	0 Ω resistors (0603)
U1	1	MAX9589AUB+ (10-pin μ MAX)
—	1	PCB: MAX9589 Evaluation Kit+

Component Suppliers

SUPPLIER	PHONE	WEBSITE
Murata Mfg. Co., Ltd.	770-436-1300	www.murata.com
Taiyo Yuden	800-348-2496	www.t-yuden.com
TDK Corp.	847-803-6100	www.component.tdk.com

Note: Indicate that you are using the MAX9589 when contacting these component suppliers.

Features

- ◆ Quad Channel (2 CVBS and S-Video)
- ◆ AC-Coupled
- ◆ 7MHz \pm 1dB Passband
- ◆ 40dB Attenuation at 27MHz
- ◆ 2.7V to 3.6V Single-Supply Operation
- ◆ Fully Assembled and Tested

Ordering Information

PART	TEMP RANGE	IC PACKAGE
MAX9589EVKIT+	0°C to +70°C*	10 μ MAX [®]

+Denotes a lead-free and RoHS-compliant EV kit.

*This limited temperature range applies to the EV kit PCB only.

The MAX9589 IC temperature range is -40°C to +125°C.

μ MAX is a registered trademark of Maxim Integrated Products, Inc.

Quick Start

Recommended Equipment

- A DC power supply capable of supplying a voltage between 2.7V to 3.6V at 500mA
- CVBS and S-video signal generator
- Video measurement equipment (e.g., Tektronix VM700T or equivalent)

Procedure

The MAX9589 EV kit is fully assembled and tested. Follow the steps below to verify board operation.

Caution: Do not turn on the power supply until all connections are completed.

- 1) Connect the power supply to the pads labeled VDD and GND on the MAX9589 EV kit.
- 2) Connect the desired test signals from the video signal generator to the IN_A/CVBS, IN_B/CVBS, IN_C/LUMA(Y), and IN_D/CHROMA(C) BNC connectors.
- 3) Connect the output signals from the OUT_A, OUT_B, OUT_C, and OUT_D BNC connectors to the inputs of the video measurement equipment.
- 4) Turn on the power supply and verify the output signals.

MAX9589 Evaluation Kit

Detailed Description

The MAX9589 EV kit demonstrates the MAX9589 low-power, quad-channel video filter amplifier with integrated reconstruction filters. The EV kit operates from 2.7V to 3.6V with a 2V/V fixed gain.

The MAX9589 has $\pm 1\text{dB}$ (typ) passband flatness at 7MHz and 40dB attenuation at 27MHz and the outputs can be DC-coupled to a 75 Ω load, which is the equivalent of two video loads, or AC-coupled to a 150 Ω load.

AC-Coupling the Output

The output of the MAX9589 can be AC-coupled. To keep the highpass formed by the 150 Ω equivalent resistance of the video transmission line to a corner frequency of 4.8Hz or lower, remove the 0 Ω resistors on R9–R12 and install $\geq 220\mu\text{F}$ coupling capacitors on the C7–C10 pads.




Figure 1. MAX9589 EV Kit Schematic

MAX9589 Evaluation Kit

Evaluates: **MAX9589**




Figure 2. MAX9589 EV Kit Component Placement Guide—Component Side




Figure 3. MAX9589 EV Kit PCB Layout—Component Side

MAX9589 Evaluation Kit




Figure 4. MAX9589 EV Kit PCB Layout—Solder Side

Maxim cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in a Maxim product. No circuit patent licenses are implied. Maxim reserves the right to change the circuitry and specifications without notice at any time.

4 _____ **Maxim Integrated Products, 120 San Gabriel Drive, Sunnyvale, CA 94086 408-737-7600**