

## NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

(IF PRESENT)

**OPERATING TEMPERATURE:** 


SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT SIGNAL CONTACT RESISTANCE:

INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE:


30A (CURRENT) POWER/CO-AX CONTACT RATING:  $10m\Omega$  MAX.

5000MΩ min.

1000V AC rms



	COMBINATION D-SUB		SW REFERENCE NO.: 629 COMBO ASSEMBLY		
			DRAWN: C.B	DATE: JAN. 01/20	19
			CHECKED:	DATE:	
	EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INCAND	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2
5 -	YOUR CONNECTION TO QUALITY & SERVICE	SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	DRAWING NUMBER: 629-13W3640-3NE		ISSUE
			PART NUMBER: 629-13W	3640-3NE	1





THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY. STEEL, NICKEL PLATED COPPER ALLOY, 30µ" GOLD PLATED -55°C ~ 125°C

THERMOPLASTIC POLYESTER, UL94V-0

TOLERANCE UNLESS OTHERWISE SPECIFIED .X ±0.25 .XX ±0.13 .XXX ±0.05

