ב בר			0			
A Z					2	
			LAYOUT SHOWN AS EXAMP	PLE	3	
	Keying Shown as example					
CHARACTERISTICS	Connector dimension					
-Standard : Based on MIL-DTL-38999 Series III	Dim Nominal					
-Shell Material : Aluminium -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8μm minimum	Shell MaterialAluminiumØS44.9 Max-Shell PlatingNickelZ31 Max-Shell PlatingNickelVV THREADM34x1-6g-Insulator: ThermoplasticWV THREADM34x1-6g-Contacts: Copper Alloy: Silicon ElastomerSilicon Elastomer					
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories			PN: 8D523F06AB			
-Temperature Range : -65°C to +200°C		A 06-10-2016	First Release			
-Salt Spray : 48 hours		ISS DATE	Latest modification - by		MOD N°	
		Designed By:	Date:	CUSTOMER DRAWING		
		TITLE	Aluminium Plug 8D series			
BASIC SERIES: 8D 5 - 23 F 0 SHELL TYPE : Plug with RFI Shielding	16 A B	SCALE -{	General linear Tolerances: ±	NPRDS / PROJECT 859		
CONTACT TYPE : Standard Crimp Contact				SOURIAU This document is the property of SOURIAU it must not be reproduced or communicated without permission		
PLATING : F = Nickel	CONTACT LAYO		SOURIAU DR		SHEET	
		A3	8D523F06A		1/2	

	т	۵	г т	m	Ū	0
		Contact Layout				
		06				
4						
	é	6#8 Concentric Twinax Service M				
		23-06	1			
	Ctc	X Y	-			
	A	0 9.24	-			
	В	8.81 2.87	1			
	С	5.43 -7.49]			
ω	D	-5.43 -7.49				
	E	-8.81 2.87	-			
	F	0 0				
						SOURIAU shall not be liable for an
						due to a use of the Products w
						the Specifications issued by either o (professional recommenda
						(professional recommenda
N						Count FR
						PN: 8D523
					A 06-10-20	16 First Release
					ISS DATE	Latest modification - by
					Designed By:	Date:
					TITLE	Alumir
					SCALE	General linear
_					NA	Tolerances:
					SOURIA	U WWW.SOURIAU.C
					FORMAT	
					A3	SOURIAU 8D523F
L	Н	G	F	E	D	C
				\backslash	V	

