

# GMA.2B.050.DG

## SUMMARY

#### # Wires



Image is for illustrative purpose only

Series	2B	
Termination type	No contacts / Accessory	
IP rating	0	
AWG wire size	0.00 - 0.00	
Cable Ø	5.00 - 5.50 mm	
Status	active	

#### Download

Request a quote Catalog

# **TECHNICAL DETAILS**

#### **Mechanics**


Shell Style/Model Keying	GMA*: Bend relief Grey No keying
Housing Material	Thermoplastic polyurethane elastomer (Elastollan 1185 A)
Variant	G : Gray
Weight	1.66 g
Performance Configuration Insulator Rated Current	G: PEEK/Pehd

#### Others

Temp (min / max): -40°C / +80°C

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

### **DRAWINGS**



No keying

#### Dimensions

	А	L
mm.	5.0	36
in.	0,20	1,42

### **RECOMMENDED BY LEMO**

#### Tools

#### Cables

120222		
130777		
IJULLL		

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.