

Specification Sheet

Part Number: 170-03070



Braided Sleeving, Expandable, .25" Dia, PA66 Monofilament, Black, 1000 ft/bulk reel

Article Number	170-03070
Туре	BSPA66140B
Color	Black (BK)
Features & Benefits	 Resists fuels, salts and solvents, gasoline, and other common contaminants. Nylon monofilament construction weave offers a tight, 12 mil braid that provides full coverage but will not rot or retain moisture. Material performs well in wet applications and where abiding substrate has a smooth surface. Expands up to 150% of flat diameter for easy installation.
Quantity Per	reel

Product Description

A pliable yet durable nylon sleeve that protects against cuts, abrasion and excessive wear caused by repetitive motion. Used on hoses, pipes, wiring harnesses and cables installed in cars, trucks, military vehicles, trains and industrial equipment. Protects delicate wiring in engine compartments and near exhaust systems or used to organize wires and breakouts in electrical harnesses.

Short Description	Braided Sleeving, Expandable, .25" Dia, PA66 Monofilament, Black, 1000 ft/bulk reel
Global Part Name	BSPA66140B-PA66-BK
Length L (Imperial)	1000.0
Length L (Metric)	304.8
Bundle Diameter Min (Imperial)	0.125
Bundle Diameter Min (Metric)	3.2
Bundle Diameter Max (Imperial)	0.375
Bundle Diameter Max (Metric)	9.5
Diameter D (imperial)	0.25
Diameter D (metric)	6.4
Nominal Diameter (Imperial)	1/4
Nominal Diameter (Metric)	6.4
Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	Non-Flammable

Halogen free	Yes
Operating Temperature (Metric)	-49°F to +302°F (-45°C to +150°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	1000
Package Quantity (Metric)	304.80
Customs Number	5808100000
Weight (Metric)	1.41
Weight (Imperial)	3.1

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions

^{© 2019} HellermannTyton. All Rights Reserved.