


# CABLE-D25SUB/B/2X14/500/TU812

Order No.: 2304678



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2304678>

Splitting cable for ABB S800 I/O, cable length 5 m

| Commercial data          |   |
|--------------------------|---|
| GTIN (EAN)               | <br>4 017918 951351 |
| Note                     | Made-to-order   |
| sales group              | I680  |
| Pack                     | 1 pcs.  |
| Customs tariff           | 85444290  |
| Catalog page information | Page 189 (IF-2009)  |

### Product notes

WEEE/RoHS-compliant since:  
01/01/2006



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

## Technical data

| General                                 |                  |
|---|------------------|
| Nominal voltage $U_N$                   | < 50 V AC        |
|   | 60 V DC          |
| Max. current carrying capacity per path | 1 A              |
| Max. conductor resistance               | 0.16 $\Omega$ /m |
| Ambient temperature (operation)         | -20 °C ... 50 °C |

|   |   |
|---|---|
| Ambient temperature (storage/transport)       | -20 °C ... 70 °C                                    |
| Number of positions, control side             | 25  |
| Number of connectors, control side            | 1   |
| Number of positions, module side              | 14  |
| Number of connectors, modul side              | 2   |
| Fixed cable length                            | 5 m   |
| Single wire, cross section                    | 0.14 mm <sup>2</sup>                                |
| Conductor construction: Number of litz wires: | 7   |
| Single wire, material                         | Cu tin-plated                                       |
| External diameter                             | 6.3 mm  |
| Cable, preassembly                            | Insulation displacement, IEC 60352-4/DIN EN 60352-4 |
| Shielding                                     | no  |

**Address**

PHOENIX CONTACT Deutschland GmbH  
Flachmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact  
Technical modifications reserved;