		D	0	₩ >]
Z Z D D D D D D D D D D D D D D D D D D						4
	The second second		LAYOUT SHOWN AS EXAM	APLE		3
	Keying Shown as example					
CHARACTERISTICS	Connector dimension					
-Standard : Based on MIL-DTL-38999 Series III	Dim Nominal ØS 29.4 Max	[
 -Shell Material : Aluminium -Shell Plating : Olive drab Cadmium -Insulator : Thermoplastic -Contacts : Copper Alloy 	Z 31 Max VV THREAD M18x1-6g		SOURIAU shall not be liable for any no due to a use of the Products which the Specifications issued by either of th (professional recommendation	does not comply with e Parties or by a third party		
-Seals & Grommet : Silicon Elastomer			Country FR	Jurisdiction & Control List Not Listed		2
-Contact Plating : Gold over copper Alloy 0.8μm minimum -Durability : 500 Mating cycles						
-Delivered without Souriau contacts			PN: 8D513W0	8SNL		
-Temperature Range : -65°C to +175°C		A 19-10-2016	First Release			-
-Salt Spray : 500 hours		ISS DATE	Latest modification - by		MOD N°	
Mass : 23.4 g ± 10%		Designed By:	Date:	CUSTOMER DRAWING		╞
		TITLE	Aluminiu	m Plug 8D series		
BASIC SERIES: 8D 5 - 13 W 0	08 S N L	SCALE	General linear	NPRDS / PROJECT		_
BASIC SERIES: 8D 5 - 13 W C	08 S N L Delivered W/O Contacts	NA	Tolerances:	859		
CONTACT TYPE : Standard Crimp Contact	ORIENTATION : N	-		This document is the prop SOURIAU	erty of	_
SHELL SIZE : 13	CONTACT TYPE : SOCKET(500 Matings)	SUURIAU	WWW.SOURIAU.CO	M it must not be reproduce communicated without per		
	CONTACT LAYOUT : 13-08	•			SHEET	_
DIATING : W - Olive drah Cadmium	CUNTACT LATUUT : 13-08		SOURIAU D		JILLI	
PLATING : W = Olive drab Cadmium		A3	8D513W08	SNI -C	1/2	

		۵	г	m		0	
		Contact Layout					
4	×	$ \begin{array}{c} & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & $					
	Com posi IC A B C C D C F F F G G H	Jon (mm) X-axis (mm) Y-axis (mm) +.065 (1.65) +.157 (3.99) +.170 (4.32) +.000 (0.00) +.120 (3.05) 120 (3.05) 120 (3.05) 170 (4.32) 120 (3.05) 120 (3.05) 120 (3.05) 120 (3.05) 120 (3.05) 120 (3.05) 170 (4.32) +.000 (0.00) 065 (1.65) +.157 (3.99)					
പ	size no. co	mber of Size Service Contact Supersede ntacts contacts rating location 8 20 I All MS20051-					
	F						
						SOURIAU shall not be liable for due to a use of the Products the Specifications issued by either (professional recommend	wl r o
N						Cou F	nti R
						PN: 8D513	V
						16 First Release	
_					ISS DATE Designed By:	Latest modification - by Date:	
					TITLE	Alum	ir
					SCALE NA	General linear Tolerances:	
					SOURIA		.0
					FORMAT A3	SOURIA	
l	Н	G	F	E		8D513V	V
					V		_

	Ξ		Þ			
						4
						3
whic r of t	non-conformit h does not co he Parties or t n, technical n	mply wi	th d party			
intry R	Jurisd	iction & Not Li	Control List sted			2
W	D8SNL					-
		CUST		N	NOD N°	
customer drawing ninium Plug 8D series						
ır	NPRDS / PROJECT					
			859			1
.CC	.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission				r	
	DRG N° 8SNL-C				SHEET 2/2	
VU	BSINE-C		A		-, -	J
	5		· ^			