

Product data sheet

Characteristics

NSYAMRD19357TB

Symmetrical DIN rail, H35xD7.5 mm Length: 168 mm, for boxes of 175 mm (Internal)



Main

Range	Thalassa
Accessory / separate part category	Installation accessory
Product or Component Type	Rail
Device Application	Multi-purpose
For enclosure nominal dimensions	-
Quantity per package	Set of 10

Complementary

Type of rail	Symmetrical DIN
Range compatibility	Thalassa TBS Thalassa TBP
Device composition	1 rail
Material	steel
Surface Finish	Zinc coated
Length	Real 6.61 in (168 mm) Internal box height or width 6.89 in (175 mm)
Height	1.38 in (35 mm)
Width	0.30 in (7.5 mm)
Thickness	0.04 in (1 mm)
Net Weight	0.12 lb(US) (0.056 kg)

Ordering and shipping details

Category	80036-ENCLOSURE SYSTEMS ACCESSORIES
Discount Schedule	ES1
GTIN	3606480166242
Nbr. of units in pkg.	1
Package weight(Lbs)	1.98 oz (56.0 g)
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	0.79 in (2 cm)
Package 1 width	7.87 in (20 cm)
Package 1 Length	10.24 in (26 cm)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------