

pushbutton, high, clear, for illuminated pushbutton



| | |
|--|--|
| product brand name | SIRIUS ACT |
| product designation | Button |
| design of the product | raised |
| product type designation | 3SU1 |
| Actuator | |
| outer diameter of the actuating element | 23.7 mm |
| Substance Prohibitance (Date) | 10/01/2014 |
| Ambient conditions | |
| ambient temperature | 70 ... -25 °C |
| <ul style="list-style-type: none"> during operation during storage and transport | -40 ... +80 °C |
| environmental category during operation according to IEC 60721 | 3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 ... 95%) |
| Installation/ mounting/ dimensions | |
| depth | 7.4 mm |
| Accessories | |
| material of accessory | Plastic |
| color of accessory | clear |
| Certificates/ approvals | |
| General Product Approval | Declaration of Conformity |



[Confirmation](#)



Test Certificates

Marine / Shipping

[Type Test Certificates/Test Report](#)



other

[Environmental Conformations](#)

[Confirmation](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=3SU1901-0FS70-0AA0>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mfb=3SU1901-0FS70-0AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SU1901-0FS70-0AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mfb=3SU1901-0FS70-0AA0&lang=en

last modified:

4/4/2022 