



.XX ±0.13

.XXX ±0.05



ISSUE NUMBER 1 ORIGINAL





S

MATERIAL: HOUSING: SHELL: CONTACT:	THERMOPLASTIC POLYESTER, UL94V-0 STEEL, TIN PLATED COPPER ALLOY, GOLD FLASH PLATED
OPERATING TEMPERATURE:	-55°C ~ 125°C
POWER/CO-AX CONTACT RATING: (IF PRESENT)	40A (CURRENT)
SIGNAL CONTACT CURRENT RATING	: 5A PER CONTACT
SIGNAL CONTACT RESISTANCE:	10mΩ MAX.
INSULATOR RESISTANCE:	5000MΩ min.
DIELECTRIC	
WITHSTANDING VOLTAGE:	1000V AC rms


COMBINATION D-SUB		SW REFERENCE NO.: 630 C	OMBO ASSEMBLY	
		DRAWN: C.B	DATE: JAN. 01/20	19
		CHECKED:	DATE:	
EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INCAND	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2
TORONTO, ONTARIO CANADA	SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE	DRAWING NUMBER: 630-7W2-	-250-4T1	ISSUE
O QUALITY & SERVICE	PART NUMBER 630-7W2	-250-4T1	1	

PART NUMBER:



20.33







MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

630-7W2-250-4T1

